

OVERVIEW



| | |
|----------------------------------|---------------------------------|
| 1. Smart card reader * | 5. HDMI |
| 2. USB-A (USB 5Gbps) | 6. 2x Thunderbolt 4 |
| 3. Ethernet (GbE RJ-45) | 7. USB-A (USB 5Gbps), Always On |
| 4. Kensington Nano Security Slot | 8. Headphone jack (3.5mm) |

Notes:

- Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

Intel® H Series Core Ultra 5 / 7 / 9 Processor (Series 2); supports up to 16 cores; up to 5.4GHz; base TDP ratings of up to 50W (without discrete GPU loading or integrated graphics only model) / 25W (with discrete GPU loading)

Processor**^[1]

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics | Intel® vPro® Eligibility | NPU | Overall TOPS |
|-------------------|---------------------------------------|---------|---|---|-------|-------------------------------------|--------------------------|--------------------------------|---------------|
| Core Ultra 5 225H | 14 (4 P-core + 8 E-core + 2 LPE-core) | 14 | P-core 1.7GHz / E-core 1.3GHz / LPE-core 700MHz | P-core 4.9GHz / E-core 4.3GHz / LPE-core 2.5GHz | 18MB | Intel® Arc™ 130T GPU, up to 63 TOPS | - | Intel® AI Boost, up to 13 TOPS | Up to 83 TOPS |
| Core Ultra 5 235H | 14 (4 P-core + 8 E-core + 2 LPE-core) | 14 | P-core 2.4GHz / E-core 1.8GHz / LPE-core 700MHz | P-core 5.0GHz / E-core 4.4GHz / LPE-core 2.5GHz | 18MB | Intel® Arc™ 140T GPU, up to 74 TOPS | Intel® vPro® Enterprise | Intel® AI Boost, up to 13 TOPS | Up to 94 TOPS |
| Core Ultra 7 255H | 16 (6 P-core + 8 E-core + 2 LPE-core) | 16 | P-core 2GHz / E-core 1.5GHz / LPE-core 700MHz | P-core 5.1GHz / E-core 4.4GHz / LPE-core 2.5GHz | 24MB | Intel® Arc™ 140T GPU, up to 74 TOPS | - | Intel® AI Boost, up to 13 TOPS | Up to 96 TOPS |
| Core Ultra 7 265H | 16 (6 P-core + 8 E-core + 2 LPE-core) | 16 | P-core 2.2GHz / E-core 1.7GHz / LPE-core 700MHz | P-core 5.3GHz / E-core 4.5GHz / LPE-core 2.5GHz | 24MB | Intel® Arc™ 140T GPU, up to 75 TOPS | Intel® vPro® Enterprise | Intel® AI Boost, up to 13 TOPS | Up to 97 TOPS |
| Core Ultra 9 285H | 16 (6 P-core + 8 E-core + 2 LPE-core) | 16 | P-core 2.9GHz / E-core 2.7GHz / LPE-core 1GHz | P-core 5.4GHz / E-core 4.5GHz / LPE-core 2.5GHz | 24MB | Intel® Arc™ 140T GPU, up to 77 TOPS | Intel® vPro® Enterprise | Intel® AI Boost, up to 13 TOPS | Up to 99 TOPS |

Notes:

^[1] Intel® vPro® platform requires an eligible Intel® processor, a supported operating system, Intel® LAN and / or WLAN silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. For detailed vPro® support information, please refer to the System Management section.

AI (Artificial Intelligence)

AI PC Category

AI-Ready Workstations

NPU

Integrated Intel® AI Boost, up to 13 TOPS

Operating System

Operating System

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Ubuntu Linux
- Red Hat Enterprise Linux 10 (certified only, for detailed and latest information, please visit [Red Hat Certified Hardware](#))^[1]

Notes:

^[1] Red Hat Enterprise Linux 10 certification will be available in November 2025.

Graphics

Graphics

| Graphics | Type | Memory | TGP |
|--|------------|-----------|---------------|
| Intel® Arc™ 130T GPU | Integrated | Shared | Share CPU TDP |
| Intel® Arc™ 140T GPU | Integrated | Shared | Share CPU TDP |
| NVIDIA® RTX PRO 500 Blackwell Generation 6GB GDDR7 Laptop GPU | Discrete | 6GB GDDR7 | 35W |
| NVIDIA® RTX PRO 1000 Blackwell Generation 8GB GDDR7 Laptop GPU | Discrete | 8GB GDDR7 | 35W |

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via Thunderbolt™ 4 and HDMI®).

Max resolution for multiple external display:

- 3x 3840x2160@60Hz (Thunderbolt™ 4 and HDMI®)

Max resolution for single external display:

- Thunderbolt™ 4 supports up to 7680x4320@60Hz
- HDMI® supports up to 3840x2160@60Hz

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

Up to 96GB (2x 48GB DDR5 CSODIMM)

Memory Slots

Two DDR5 SODIMM / CSODIMM slots, dual-channel capable

Memory Type**

- DDR5-5600 SODIMM, non-ECC, maximum transfer speeds of up to 5600 MT/s, 8GB / 16GB / 32GB memory modules are available
- DDR5-6400 CSODIMM, non-ECC, maximum transfer speeds of up to 6400 MT/s, 32GB / 48GB memory modules are available

Storage

Max Storage Support^[1]

Up to one 2TB M.2 2280 Gen 5 Performance SSD

Storage Slot^[2]

One M.2 2280 PCIe® 4.0 x4 slot

Storage Type**

| Disk Type | Interface | Offering | Security |
|--------------|--|---------------------|----------|
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 4.0 x4 | 256GB / 512GB / 1TB | Opal 2.0 |
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 5.0 x4 Performance ^[3] | 512GB / 1TB / 2TB | Opal 2.0 |

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

[2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.

PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);

PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);

PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

[3] Gen 5 SSD on M.2 PCIe® 4.0 slot will run on PCIe® 4.0 protocols.

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby Audio™

Microphone

Dual-microphone array, Dolby Voice®

Camera**

- 5.0MP + IR with privacy shutter and Ultrasonic Human Presence Detection, fixed focus, temporal noise reduction
- 5.0MP + IR with privacy shutter, fixed focus, temporal noise reduction
- 5.0MP with privacy shutter, fixed focus, temporal noise reduction

Battery

Battery**

- 57Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)
- 75Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)

Power Adapter

Power Adapter^[1]

100W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**

| Size | Resolution | Touch | Type | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features |
|-------|-------------------|-------------------|------|------------|-----------------------------|--------------|----------------|-------------|--------------|-------------------------|---|
| 14.5" | WUXGA (1920x1200) | Non-touch | IPS | 400 nits | Anti-glare | 16:10 | 1000:1 | 45% NTSC | 60Hz | 85° / 85° / 85° / 85° | 88% screen to body ratio, AICCP color calibration, Low Blue Light, Eyesafe® 2.0 Certified, DC dimming |
| 14.5" | WUXGA (1920x1200) | Add-on Film Touch | IPS | 400 nits | Anti-glare Anti-fingerprint | 16:10 | 1000:1 | 45% NTSC | 60Hz | 85° / 85° / 85° / 85° | 88% screen to body ratio, AICCP color calibration, Low Blue Light, Eyesafe® 2.0 Certified, DC dimming |
| 14.5" | WQXGA (2560x1600) | Non-touch | IPS | 400 nits | Anti-glare | 16:10 | 1500:1 | 100% sRGB | 90Hz | 85° / 85° / 85° / 85° | 88% screen to body ratio, X-Rite® |

| | | | | | | | | | | | |
|-------|----------------|-----------|-----|----------|------------|-------|--------|-------------|-------|-----------------------|---|
| | | | | | | | | | | | Factory Color Calibration, Low Blue Light, Eyesafe® 2.0 Certified, DC dimming |
| 14.5" | 3K (3072x1920) | Non-touch | IPS | 500 nits | Anti-glare | 16:10 | 1500:1 | 100% DCI-P3 | 120Hz | 85° / 85° / 85° / 85° | 88% screen to body ratio, TCON Color Calibration Low Blue Light, Eyesafe® 2.0 Certified |

Touchscreen

- Add-on Film Touch, supports 10-point touch (selected WUXGA display)
- Non-touch

Screen-to-Body Ratio

88%

Color Calibration**

- AICCP color calibration (WUXGA display)
- TCON factory color calibration (3K display)
- X-Rite® factory color calibration (WQXGA display)

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, Copilot key

Keyboard Backlight

LED backlight

UltraNav™

3-button TrackPoint® pointing device and glass-like Mylar® surface multi-touch TrackPad, 60 x 115 mm (2.36 x 4.53 inches)

Mechanical

Dimensions (WxDxH)^[1]

325.5 x 227.6 x 11.2 / 15.1 (front / rear), 21.7 (maximum) mm
12.81 x 8.96 x 0.44 / 0.59 (front / rear), 0.85 (maximum) inches

Weight^[2]

| Models | Weight |
|---------------------------------|--------------------------------|
| Models with integrated graphics | Starting at 1.60 kg (3.53 lbs) |
| Models with discrete graphics | Starting at 1.64 kg (3.61 lbs) |

Case Color

Black

Case Material

Aluminium (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®**^[1]

- Intel® Wi-Fi® 7 BE201, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4
- Intel® Wi-Fi® 7 BE201, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, Intel® vPro® technology support

WWAN

No support

SIM Card

No physical SIM card inbox

Ethernet**

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

NFC

No support

Notes:

[1] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

Ports^[1]

Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (GbE RJ-45)
- 1x Security keyhole
- 2x Thunderbolt™ 4, with USB PD 3.0

Optional Ports

1x Smart card reader

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

Fingerprint Reader

Touch style fingerprint reader integrated in power button, match-on-chip

BIOS Security

- NVMe[®] password
- Power-on password
- Supervisor password
- Self-healing BIOS

Other Security

- Bottom cover tamper detection
- Camera privacy shutter
- (Optional) Ultrasonic Human Presence Detection for IR camera
- (Optional) IR camera for Windows[®] Hello (facial recognition)

MANAGEABILITY

System Management

System Management

- Intel[®] vPro[®] Enterprise
- Non-vPro[®]

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

ACCESSORIES

Bundled Accessories

Bundled Accessories

- Lenovo[®] HDMI[®] to VGA Monitor Adapter
- Lenovo[®] USB-C[®] to DisplayPort[™] Adapter
- Lenovo[®] USB-C[®] to Ethernet Adapter (1Gbps)
- Lenovo[®] USB-C[®] to VGA Adapter

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping packaging: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material^[1]

- 85% PCC recycled plastic used in key caps
- 90% PCC recycled plastic used in speaker enclosure
- 90% PCC recycled plastic used in the battery
- 90% PCC recycled plastic used in 100W adapters
- 80% CU recycled thermal block

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS

Green Certifications^[1]

Green Certifications^[2]

- ENERGY STAR® 9.0
- EPEAT™ Gold Registered
- RoHS compliant
- TCO Certified, generation 10

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

- Eyesafe® Certified 2.0
- TÜV Rheinland® Low Blue Light

ISV Certifications

ISV Certifications

Please visit [ISV certifications for Lenovo® Workstations](#)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

