



HP ZBook 8 G2i 14 inch Mobile Workstation PC



Front

- | | | | |
|---|-------------------------|---|------------|
| 1 | Internal Microphone (2) | 4 | Webcam LED |
| 2 | Webcam | 5 | Touchpad |
| 3 | Camera Shutter | | |





Sides

1	HDMI 2.1	7	Nano SIM card slot (optional)
2	Thunderbolt™ 4 with (USB Power Delivery, DisplayPort™ 2.1) ¹	8	Power Indicator LED
3	Thunderbolt™ 4 with (USB Power Delivery, DisplayPort™ 2.1) ¹	9	USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
4	Power Indicator LED	10	USB Type-A 5Gbps signaling rate (Data only)
5	Headphone/mic combo jack	11	RJ45 Ethernet port
6	Smart Card Reader (optional)	12	Nano Security Lock slot

1. USB 20Gbps signaling rate is not available with Thunderbolt™ 4. Actual throughput may vary.

PRODUCT NAME

HP ZBook 8 G2i 14 inch Mobile Workstation PC



OPERATING SYSTEM

Preinstalled

FreeDOS

Ubuntu Linux 24.04

Windows 11 Home - HP recommends Windows 11 Pro for business ¹

Windows 11 Home Single Language - HP recommends Windows 11 Pro for business ¹

Windows 11 Pro ¹

Windows 11 Pro (Windows 11 Enterprise available with a Volume Licensing Agreement) ¹

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>



PROCESSORS

Processor	Cores	Number of P-cores	Number of E-cores	Number of LPE-cores	Threads	Smart Cache	Max Turbo Frequency			Intel SIPP/vPro® Enterprise	Integrated Graphic	NPU
							P-cores	E-cores	LPE-cores			
Intel® Core™ Ultra 9 386H processor	16 cores	4	8	4	16	18 MB	4.90 GHz	3.70 GHz	3.50 GHz	X	Intel® Graphics	50 TOPS
Intel® Core™ Ultra 7 366H processor <small>2,3,4,5,6</small>	16 cores	4	8	4	16	18 MB	4.80 Ghz	3.60 Ghz	3.40 GHz	X	Intel® Graphics	50 TOPS
Intel® Core™ Ultra 7 356H processor <small>2,3,5,6</small>	16 cores	4	8	4	16	18 MB	4.70 GHz	3.50 GHz	3.30 GHz		Intel® Graphics	50 TOPS
Intel® Core™ Ultra 5 336H processor <small>2,3,4,5,6</small>	12 cores	4	4	4	12	18 MB	4.60 GHz	3.40 GHz	3.20 GHz	X	Intel® Graphics	47 TOPS
Intel® Core™ Ultra 5 338H processor <small>2,3,4,5,6</small>	12 cores	4	4	4	12	18 MB	4.70 GHz	3.40 GHz	3.30 GHz	X	Intel® ARC™ B370 GPU Intel® ARC™ Pro B370 GPU	47 TOPS



Intel® Core Ultra X9 388H processor	16 cores	4	8	4	16	18 MB	5.10 GHz	3.80 GHz	3.70 GHz	X	Intel® ARC™ B390 GPU Intel® ARC™ Pro B390 GPU	50 TOPS
Intel® Core Ultra X7 368H processor 2,3,4,5,6	16 cores	4	8	4	16	18 MB	5.00 GHz	3.80 GHz	3.60 GHz	X	Intel® ARC™ B390 GPU Intel® ARC™ Pro B390 GPU	50 TOPS
Intel® Core Ultra X7 358H processor 2,3,5,6	16 cores	4	8	4	16	18 MB	4.80 Ghz	3.50 GHz	3.30 GHz		Intel® ARC™ B390 GPU	50 TOPS
Intel® Core™ Ultra 7 365 processor 2,3,4,5,6	8 cores	4	0	4	16	12 MB	4.80 Ghz	NA	3.60 GHz	X	Intel® Graphics	49 TOPS
Intel® Core™ Ultra 7 355 processor 2,3,5,6	8 cores	4	0	4	8	12 MB	4.70 GHz	NA	3.50 GHz		Intel® Graphics	49 TOPS
Intel® Core™ Ultra 5 335 processor 2,3,4,5,6	8 cores	4	0	4	8	12 MB	4.60 GHz	NA	3.40 GHz	X	Intel® Graphics	47 TOPS
Intel® Core™ Ultra 5 325 processor 2,3,5,6	8 cores	4	0	4	8	12 MB	4.50 GHz	NA	3.40 GHz		Intel® Graphics	47 TOPS



Processor Family

Intel® Core™ Ultra 9 processor

Intel® Core™ Ultra 7 processor

Intel® Core™ Ultra 5 processor

Intel® Core Ultra X9 processor

Intel® Core Ultra X7 processor

2. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel® numbering, branding, naming are not a measurement of clock speed.

3. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration.

4. For full Intel® vPro® functionality, Windows 10 (or higher) Pro or Enterprise 64 bit edition, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or WLAN card and TPM 2.0 are required. Some functionality requires additional 3rd party software in order to run. See <http://intel.com/vpro>

5. Features and software that require a NPU may require software purchase, subscription or enablement by a software or platform provider, and third party software may have specific configuration or compatibility requirements. Potential NPU inferencing performance varies by use, configuration, and other factors.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>



GRAPHICS

Integrated

Intel® ARC™ Pro B390 ⁷

Intel® ARC™ Pro B370 ⁷

Intel® Graphics ⁷

Discrete IC Chip

NVIDIA® RTX PRO™ 500 Blackwell

Supported protocols

Support DirectX® 12, HDCP 2.3, HDMI 2.1 (up to 4K 60Hz)

Display supported (including internal display; dock may be required) up to 4

[7. Intel® ARC™ graphics only available on select Intel® Core™ Ultra H-series processor-powered systems with at least 16GB of system memory in dual channel configuration.](#)



DISPLAY

Availability may vary by country.

Actual brightness will be lower with touchscreen or HP Sure View.

Non-Touch

35.6 cm (14") diagonal, WUXGA (1920 x 1200), LBL IPS anti-glare, 800 nits, , Sure View 6 sRGB 100% eDP1.5⁸

35.6 cm (14") diagonal, WQXGA (2560 x 1600),120 Hz, UWVA anti-glare, micro-edge, 500 nits, HP DreamColor eDP 1.4+PSR2

35.6 cm (14") diagonal, 2.5K (2560 x 1600), WLED+LBL IPS anti-glare, 400 nits, AD-100 eDP 1.4+PSR2

35.6 cm (14") diagonal, WUXGA (1920 x 1200), 60 Hz IPS anti-glare, 300 nits, sRGB 62.5% eDP 1.2 w/o PSR

35.6 cm (14") diagonal, WUXGA (1920 x 1200), 60 Hz WLED+LBL IPS anti-glare, 400 nits, sRGB 100% eDP1.5

Touch

35.6 cm (14") diagonal, WUXGA (1920 x 1200), LBL touch IPS anti-glare, 800 nits, , Sure View 6 sRGB 100% eDP1.5⁸

35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD touch IPS anti-glare, 400 nits, sRGB 62.5% eDP 1.2 w/o PSR

Display Size (Diagonal)

90.4 cm (35.6")

Aspect Ratio

16:10

Screen to Body Ratio

0.897

Max Hinge Open Angle

163°

8. HP Sure View integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.



DOCKING (SOLD SEPARATELY)

Docking station model name

HP Thunderbolt™ 180W G6 Dock

Total number of supported displays (incl.the notebook display)

4

Max. resolutions supported

(4) 4K @60Hz*

(2) 4K @ 120Hz*

(3) QHD @ 120Hz*

(1) QHD @ 360Hz*

Dock Connectors

1 x HDMI 2.1, 2 x DisplayPort 1.4, 1 x Thunderbolt 4, 1 x USB-C 3.2 Gen 2 DisplayPort

Technical limitations

*Requires DisplayPort 1.4 support with Display Stream Compression (DSC).

Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks.

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.



Docking station model name

HP Thunderbolt™ 100W G6 Dock

Total number of supported displays (incl.the notebook display)

4

Max. resolutions supported

(4) 4K @60Hz*

(2) 4K @ 120Hz*

(3) QHD @ 120Hz*

(1) QHD @ 360Hz*

Dock Connectors

1 x HDMI 2.1, 2 x DisplayPort 1.4, 1 x Thunderbolt 4

Technical limitations

*Requires DisplayPort 1.4 support with Display Stream Compression (DSC).

Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks.

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.



Docking station model name

HP Thunderbolt™ 280W G6 Dock

Total number of supported displays (incl.the notebook display)

4

Max. resolutions supported

(4) 4K @60Hz*

(2) 4K @ 120Hz*

(3) QHD @ 120Hz*

(1) QHD @ 360Hz*

Dock Connectors

1 x HDMI 2.1, 2 x DisplayPort 1.4, 1 x Thunderbolt 4, 1 x USB-C 3.2 Gen 2 DisplayPort

Technical limitations

*Requires DisplayPort 1.4 support with Display Stream Compression (DSC).

Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks.

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.



Docking station model name

HP USB-C™ 100W G6 Dock

**Total number of supported displays (incl.the notebook)
display)**

3

Max. resolutions supported

- (1) 4K @120hz*
- (2) 4K @120hz*
- (3) 4K @60hz*

Dock Connectors

1 x HDMI 2.1, 2 x DisplayPort 1.4

Technical limitations

*Requires DisplayPort 1.4 support with Display Stream Compression (DSC).

Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks.

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Highest resolution with dual displays is two 8K@ 30Hz host in High Resolution mode.

Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode.

The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.



STORAGE AND DRIVES

Maximum Storage

2 TB

Storage

1 TB PCIe Gen5 NVMe™ SSD Value ⁹

1 TB PCIe® Gen5x4 NVMe™ Self Encrypted OPAL2 SSD ⁹

1 TB PCIe® NVMe™ SSD Value ⁹

2 TB PCIe Gen5 NVMe™ SSD Value ⁹

256 GB PCIe® NVMe™ Self Encrypted OPAL2 SSD Value ⁹

256 GB PCIe® NVMe™ SSD Value ⁹

512 GB PCIe Gen5 NVMe™ Self Encrypted OPAL2 SSD Value ⁹

512 GB PCIe Gen5 NVMe™ SSD Value ⁹

512 GB PCIe® NVMe™ SSD Value ⁹

Secondary Storage

Storage Slots

1 x M.2 2280

RAID

RAID: Unsupported

⁹ For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 32 GB is reserved for system recovery software.



MEMORY

Maximum Memory

64GB DDR5-5600 MT/s (2 x 32 GB)¹⁰

64GB - LPDDR5X 8533 (onboard)¹⁰

RAM Support

RAM Support : 16GB, 24GB, 32GB, 64GB

Memory

64GB DDR5-5600 MT/s (2 x 32 GB)

48GB DDR5-5600 MT/s (2 x 24GB)

32GB DDR5-6400 MT/s (2 x 16 GB)

32GB DDR5-5600 MT/s (2 x 16 GB)

32GB DDR5-5600 MT/s (1 x 32 GB)

24GB DDR5-5600 MT/s (1 x 24GB)

16GB DDR5-6400 MT/s (1 x 16 GB)

16GB DDR5-5600 MT/s (2 x 8 GB)

16GB DDR5-5600 MT/s (1 x 16 GB)

64GB - LPDDR5X 8533 MT/s (onboard)

32GB - LPDDR5X 8533 MT/s (onboard)

Memory Slots

2 SODIMM

System runs at 7466 MT/s

Supports Dual Channel Memory.

Memory is replaceable by customer or customer IT support.

[10. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.](#)



NETWORKING /COMMUNICATIONS

Items below may be optional.

Ethernet

Intel® I219-LM 1GbE Vpro Ethernet Controller

Intel® I219-V 1GbE Ethernet Controller

WLAN

Intel® AX211 Wi-Fi 6E Bluetooth® 5.3 WW WLAN ^{14,15}

Intel® BE211 Wi-Fi 7 Bluetooth® 6.0 non-vPro WW WLAN ¹³

Intel® BE211 Wi-Fi 7 Bluetooth® 6.0 vPro WW WLAN ¹³

WWAN

5G NR Sub-6 CAT19 ¹¹

HP 5G NR Sub-6 CAT19 HP Go Solution

LPWAN

HP RW220-GL LTE (Low Power) (CAT-1bis) ¹²

HP RW220-GL LTE (Low Power) (CAT-1bis) with GPS

NFC

NFC Mirage WNC XRAV-1

Miracast

Native Miracast Support ¹⁶

11. 5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier supported.

12. LPWAN (also called Mobile Narrowband) supports HP Protect & Trace with Wolf Connect service through the subscription term,



but does not support mobile broadband use.

13. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11BE) functionality requires compatible Windows OS, select processor, and a Wi-Fi 7 router, sold separately. Wi-Fi 7 is backwards compatible with prior 802.11 specs. Available in countries where Wi-Fi 7 is supported. The specification for 802.11BE is a draft specification and is not final. If the final specification differs from the draft specification, it may affect the ability of the device to communicate with other 802.11BE devices.

14. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

15. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

16. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.



AUDIO/MULTIMEDIA

Privacy panel is only available on select models.

Audio

Audio by Poly Studio

2 Integrated stereo speakers

Discrete Amplifiers

2 Integrated dual array microphone

Speaker Power

1W / 8 ohm per speaker

Camera

5MP HDR camera

5MP HDR camera with Image Signal Processing (ISP) and AI Presence Detection, IR camera

Sensors

Ambient Light Sensor

Color Sensor with Ambient Light Sensing

Fingerprint Sensor (optional)

Hall Effect Sensor

HP Sure Platform

HP Tamper Lock

Thermal Sensor



KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium NB Keyboard, spill-resistant, Backlit, DuraKeys keyboard.

HP Premium NB Keyboard, spill-resistant, Privacy, Backlit, DuraKeys keyboard.

HP Premium Keyboard, spill-resistant, Backlit, DuraKeys keyboard.

HP Premium Keyboard, spill-resistant, Privacy, Backlit, DuraKeys keyboard.

Pointing Device

Clickpad

Microsoft Precision Touchpad Default Gestures Support

Multi-touch gesture support

Function Keys ¹⁷

ESC - System information

F1 - Display Switching

F2 - Blank or Privacy

F3 - Brightness Down

F4 - Brightness Up

F5 - Blank or Keyboard Backlight

F6 - Audio Mute

F7 - Volume Down

F8 - Volume Up

F9 - Mic Mute

F10 - Media

F11 - Programmable Key (myHP)

F12 - HOME

Power Button (with LED)

Insert

Delete

Home

End

Page up



Page down

Microsoft Copilot

Hidden Function Keys

Fn+R - Break, Fn+S - Sys Rq, Fn+C - Scroll Lock

17. Copilot+ in Windows requires Windows 11. Some features require an NPU. Timing of feature delivery and availability varies by market and device. Requires Microsoft account to log in. Where Microsoft in Windows is not available, the Copilot key will lead to the Bing search engine. See aka.ms/copilotpluspcs.



SOFTWARE AND SECURITY

Application Software

Buy Microsoft Office (Sold Separately) ¹⁸

Edge Customization

HP Connection Optimizer

HP Hotkey Support

HP Notifications

HP PC Hardware Diagnostics UEFI

HP PC Hardware Diagnostics Windows

HP Privacy Settings

HP Services Scan ¹⁹

HP Support Assistant ²⁰

HSA Fusion for Commercial

HSA Telemetry for Commercial

HP app ²¹

Poly Camera Pro

Poly Studio Desktop ²²

Manageability Features

HP Client Catalog (download) ²³

HP Client Management Script Library (download) ²⁴

HP Cloud Recovery ²⁵

HP Connect for Microsoft Endpoint Manager ²⁶

HP Driver Packs (download) ²⁷

HP Image Assistant (download) ²⁸

HP Manageability Integration Kit (download) ²⁹

HP Patch Assistant (download) ³⁰

HP Power Manager with Battery Health Manager (download) ³¹

Optional Security Features

HP Wolf Pro Security Edition

Enterprise Security Edition



Security Features

Secured-Core PC Enable ³²

Windows Hello Enhanced Sign-In Security (ESS)

HP Wolf Security for Business which includes: ³³

HP Sure Admin ³⁴

HP Sure Click ³⁵

HP Sure Recover ³⁶

HP Sure Run ³⁷

HP Sure Sense ³⁸

HP Sure Start ³⁹

HP Tamper Lock ⁴⁰

Security- TPM

Model

Model: Nuvoton NPCT760HAEYX

Firmware Version

Firmware Version: 7.2.4.1

TCG

TCG TPM 2.0

FIPS 140-3 Compliant

FIPS 140-3 Compliant: Yes

Model

Model: STMicro ST33KTPM2X32DKG9

Firmware Version

Firmware Version: 9.257



TCG

TCG TPM 2.0

FIPS 140-3 Compliant

FIPS 140-3 Compliant: Yes

BIOS

Absolute Persistence Module ⁴¹

Audio Permanent Disable

HP BIOS Update via Network

HP BIOSphere ⁴²

HP DriveLock & Automatic DriveLock

HP Fingerprint Sensor

HP Secure Erase ⁴³

HP Wake on WLAN

Smartcard Reader

Model number

Alcorlink IC, CR, AK9563E66-GAF-GR, QFN28

FIPS 201-3 Compliant

FIPS 201-3 Compliant: Yes

IPv6 Support

Yes

FirstNet Certified

Yes

Does the BIOS implement the ISO/IEC 19678:2015 (formerly NIST 800-147) guidelines?

Yes



UEFI version

2.9

Class

3

18. Microsoft 365 sold separately and requires Internet access for activation.

19. HP Services Scan automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights and is available preinstalled on select products, thru HP Factory Configuration Services; or it can be downloaded. For more information about how to enable HP Smart Support or for download, please visit

<http://www.hp.com/smart-support>.

20. HP Support Assistant is available on Windows. For more information, please visit www.support.hp.com/help/hp-support-assistant.

21. HP app requires Windows 10 or higher OS.

22. Poly Studio Desktop requires a Windows OS.

23. HP Client Catalog not preinstalled, however available for download at (<https://www.hp.com/us-en/solutions/client-management-solutions.html>).

24. HP Client Management Script Library (<https://www.hp.com/us-en/solutions/client-management-solutions.html#tab=manageability-tools>).

25. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, network connection. Note: You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail, please refer to: <https://support.hp.com/us-en/document/c05115630>.

26. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.

27. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

28. HP Image Assistant not preinstalled, however available for download at (<https://ftp.ext.hp.com/pub/caps-softpaq/cmit/HPIA.html>)

29. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.

30. HP Patch Assistant available on select HP PCs with the HP Manageability Kit that are managed through Microsoft System Center Configuration Manager. HP Manageability Integration Kit can be downloaded from

<http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

31. HP Power Manager with Battery Health can be downloaded by entering your system information here: https://support.hp.com/in-en/document/ish_4449597-3519507-16.



-
32. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.
 33. HP Wolf Security for Business requires Windows 10 or 11 Pro or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features.
 34. HP Sure Admin requires HP G8 or newer platforms, Windows 10 or higher, HP BIOS, HP Manageability Kit or KMS Service from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator
 35. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See https://bit.ly/2PrLT6A_SureClick for complete details.
 36. HP Sure Recover is available on select HP PCs and requires Windows 10 or 11 and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. HP Sure Recover Gen6 with Embedded Reimaging is an optional feature on select HP PCs which requires Windows 10 or 11 must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.
 37. HP Sure Run is available on select HP PCs and requires Windows 10 and higher.
 38. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.
 39. HP Sure Start is available on select HP PCs and requires Windows 10 and higher
 40. HP Tamper Lock can be Enabled/disabled by customers or IT administrator with administrator authority.
 41. Absolute Persistence firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>.
 42. HP BIOSphere features may vary depending on the platform and configuration.
 43. HP Secure Erase implements the methods outlined in the National Institute of Standards and Technology Special.
-



POWER

Power supply availability may vary by country.

Battery is internal and replaceable by customer. Serviceable by warranty.

Power Supply

HP 140W Slim USB-C AC power adapter

100W Wall Mount GaN USB-C AC power adapter

65W Wall Mount GaN USB-C AC power adapter

65W Standard USB Type-C® GaN AC power adapter

Battery

HP Long Life 3 cell, 68Wh Polymer

HP Long Life 8 cell, 77Wh Polymer

Battery Recharge Time

Supports battery HP Fast Charge: approximately 50% in 30 minutes ⁴⁴

Power Cord

3-wired plug- 1.0m

Battery life

Up to 16 hours and 15.0 minutes with 68Wh battery (Intel H484 12Xe U7 non-vPRO, UMA graphic, brightness set to 250nits on a WUXGA 400 nits, LCD display, (1 x 16 GB) LPDDR5X memory, 256GB SSD) ⁴⁵

Up to 14 hours and 30.0 minutes with 68Wh battery (Intel H404 4Xe U7 non-vPRO, UMA graphic, brightness set to 250nits on a WUXGA 400 nits, LCD display, (2 x 8 GB) DDR5 memory, 256GB SSD) ⁴⁵

Up to 9 hours and 30.0 minutes with 77Wh battery (Intel H484 4Xe U7 non-vPRO, DIS graphic, brightness set to 250nits on a WUXGA 400 nits, LCD display, (2 x 8 GB) DDR5 memory, 256GB SSD) ⁴⁵

Battery Weight

TBD

⁴⁴. Recharges your battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter minimum of 65 watts required for battery capacities 56Whr or less. Power adapter minimum of 100 watts required for battery capacities greater



than 56Whr and less than 83Whr. Power adapter minimum of 120 watts required for battery capacities greater than 83Whr and less than 100Whr. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

45. Mobile Mark 30 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.



WEIGHT & DIMENSIONS

Weight will vary by configuration. Does not include power adapter.

Front height measurement is near the front edge where the mechanical chassis taper begins. Back height measurement is near the rear edge where the mechanical chassis taper ends.

Product Weight

Starting at 1.425 kg (3.142 lb) with 68.00 Wh battery (UMA)

Starting at 1.709 kg (3.768 lb) with 77.00 Wh battery (DSC)

Weight will vary by configuration. Does not include power adapter.

Product Dimensions (w x d x h)⁴⁶

315.60 mm (W) x 222.00 mm (D) x mm (H front) / mm (H rear)

(12.43 in (W) x 8.74 in (D) x in (H front)/ in (H rear))

Maximum height 18.95 mm (0.75 in)

315.60 mm (W) x 222.00 mm (D) x mm (H front) / mm (H rear)

(12.43 in (W) x 8.74 in (D) x in (H front)/ in (H rear))

Maximum height 23.95 mm (0.94 in)

Pallet Dimensions (w x d x h)

Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details. For detailed packaging information, access the [HP Commercial Notebooks Packaging Guide](#).

46. Typical dimension. Actual dimension may vary +/- 0.5mm. Height may vary based on configuration. Maximum Height does not include Rubber feet.



PORTS/SLOTS

Left side

2 x Thunderbolt™ 4 with (USB Power Delivery, DisplayPort™ 2.1)⁴⁷

1 x HDMI 2.1

(Support up to 4k60Hz)

1 x 3.5mm headphone/mic combo jack

1 x Smart Card Reader (optional)

Right side

1 x USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)

1 x USB Type-A 5Gbps signaling rate (Data only)

1 x RJ45 Ethernet port (optional)

1 x Nano SIM card slot (optional)

1 x Nano Security Lock slot

⁴⁷ USB 20Gbps signaling rate is not available with Thunderbolt™ 4. Actual throughput may vary.



SERVICE AND SUPPORT

1-year warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>⁴⁸

48. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



SYSTEM UNIT

Stand - Alone Power Requirements

(AC Power)

Nominal Operating Voltage	20.0 V
Average Operating Power	
Max Operating Power	UMA < 100 W Discrete < 140 W

Temperature

Operating	Operating: 0° to 35° C (32° to 95° F) System performance may be reduced above 32°C (89.6°F)
Non - operating	Non-operating: -20° to 60° C (-4° to 140° F) System performance may be reduced above 32°C (89.6°F)

Relative Humidity

Operating	Operating: 10% to 90% (non-condensing)
Non - operating	Non-operating: 5% to 95%, 38.7° C (101.6° F) maximum wet bulb temperature

Shock

Operating	Operating: 40 G, 2 ms, half-sine
Non - operating	Non-operating: 240 G, 2 ms, half-sine

Random Vibration

Operating	Operating: 1.043 grms
Non - operating	Non-operating: 3.500 grms

Altitude (unpressurized)

Operating	Operating: 3,048 m (10,000 ft)
Non - operating	Non-Operating: 12,192 m (40,000 ft)

Industry Standard Certifications

Regulatory Model Number	HSN-I62C-4
CSA/UL 62368-1	Yes
UL 62368-1	Yes
ENERGY STAR®	Yes ¹
FCC/ICES/CISPR/VCCI	Yes
CE MARKING	Yes
GS Mark	Yes.
	Related commodity should comply with ISO 9241 Standards.



China CCC/SRRC/CEL	Yes
Taiwan BSMI/NCC	Yes
Korea KCC/KC/KES	Yes
Ukraine NSoC/TEC	Yes
EAEU Compliance	Yes
Saudi Arabian Compliance	Yes
TCO	Yes
EPEAT Gold	Yes ²
Low Blue Light	Yes
WW RoHS	Yes
CECP	NO
	These are requirements from the Category PM, which usually occur after RTP. At this stage, no requests have been received yet.
Medical EMC: IEC 60601-1-2:2014 EN60601-1-2: 2015	Yes
SEPA	NO
	These are requirements from the Category PM, which usually occur after RTP. At this stage, no requests have been received yet.
MIL - STD Testing	MIL-STD 810H ³

1 Configurations that are ENERGY STAR® qualified are identified as ENERGY STAR on HP websites and on <http://www.energystar.gov>

2. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

3. MIL STD testing is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.



DISPLAYS

Actual brightness will be lower with touchscreen or HP Sure View.

Availability may vary by country

35.6 cm (14") diagonal, WUXGA (1920 x 1200), LBL IPS anti-glare, 800 nits, Sure View 6 sRGB 100% eDP1.5	Active Area	301.590 x 188.500 mm (typ)
	Dimensions (W x H)	306.890 x 197.900 mm (max)
	Weight	230 g (max)
	Diagonal Size	14 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	1500:1 (typ)
	Refresh Rate	60Hz
	Brightness	800 nits (typ)
	Pixel Resolution	RGB
	Pixel Resolution - Format	1920x1200 (WUXGA)
	Aspect Ratio	16:10
	Backlight	WLED
	Color Gamut Coverage	sRGB 100%
	Color Depth	8
Viewing Angle	UWVA 89/89/89/89	
Low Blue Light	Yes	
Power Consumption	EBL@150nits:1.50 W (Max)	

35.6 cm (14") diagonal, WUXGA (1920 x 1200), LBL touch IPS anti-glare, 800 nits, Sure View 6 sRGB 100% eDP1.5	Active Area	301.590 x 188.500 mm (typ)
	Dimensions (W x H)	306.890 x 197.900 mm (max)
	Weight	260 g (max)
	Diagonal Size	14 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	Yes
	Contrast Ratio	1500:1 (typ)
	Refresh Rate	60Hz
	Brightness	800 nits (typ)
	Pixel Resolution	RGB



Pixel Resolution - Format	1920x1200 (WUXGA)
Aspect Ratio	16:10
Backlight	WLED
Color Gamut Coverage	sRGB 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption	EBL@150nits:1.90 W (Max)

35.6 cm (14") diagonal, WQXGA (2560 x 1600),120 Hz, UWVA anti-glare, micro-edge, 500 nits, HP DreamColor eDP 1.4+PSR2

Active Area	301.594 x 188.496 mm (typ)
Dimensions (W x H)	307.594 x 199.546 (max)
Weight	230 g (max)
Diagonal Size	14 inch
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	1200:1(typ)
Refresh Rate	120 Hz
Brightness	500 nits (typ)
Pixel Resolution	RGB
Pixel Resolution - Format	2560x1600 (WQXGA)
Aspect Ratio	16:10
Backlight	WLED
Color Gamut Coverage	DCI-P3 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	No
Power Consumption	2.88 (max) / 3.44 (max)

35.6 cm (14") diagonal, 2.5K (2560 x 1600), WLED+LBL IPS anti-glare, 400 nits, AD-100 eDP 1.4+PSR2

Active Area	301.594 x 188.496 mm (typ)
Dimensions (W x H)	306.890 x 197.900 mm (max)
Weight	200 g (max)
Diagonal Size	14 inch
Surface Treatment	Anti-Glare



Touch Enabled	No
Contrast Ratio	2000:1 (typ)
Refresh Rate	120 Hz
Brightness	400 nits (typ)
Pixel Resolution	RGB
Pixel Resolution - Format	2560x1600 (2.5K)
Aspect Ratio	16:10
Backlight	WLED
Color Gamut Coverage	Adobe RGB 100% + DCI-P3 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption	2.3 (max)/ 2.7 (max)

**35.6 cm (14") diagonal,
WUXGA (1920 x 1200), 60 Hz
IPS anti-glare, 300 nits, sRGB
62.5% eDP 1.2 w/o PSR**

Active Area	301.590 x 188.500 mm (typ)
Dimensions (W x H)	307.590 x 199.150 (max)
Weight	300 g (max)
Diagonal Size	14 inch
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	1000 : 1 (typ)
Refresh Rate	60 Hz
Brightness	300 nits (typ)
Pixel Resolution	RGB
Pixel Resolution - Format	1920x1200 (WUXGA)
Aspect Ratio	16:10
Backlight	WLED
Color Gamut Coverage	sRGB 62.5%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	No
Power Consumption	1.70 (max)/2.10(max)



35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD touch IPS anti-glare, 400 nits, sRGB 62.5% eDP 1.2 w/o PSR	Active Area	301.590 x 188.500 mm (typ)
	Dimensions (W x H)	307.590 x 199.150 mm (max)
	Weight	300 g (max)
	Diagonal Size	14 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	Yes
	Contrast Ratio	1000 : 1 (typ)
	Refresh Rate	40~60Hz
	Brightness	400 nits (typ)
	Pixel Resolution	RGB
	Pixel Resolution - Format	1920x1200 (WUXGA)
	Aspect Ratio	16:10
	Backlight	WLED
	Color Gamut Coverage	sRGB 62.5%
	Color Depth	8
	Viewing Angle	UWVA 89/89/89/89
Low Blue Light	No	
Power Consumption	3.49W Max	

35.6 cm (14") diagonal, WUXGA (1920 x 1200), 60 Hz WLED+LBL IPS anti-glare, 400 nits, sRGB 100% eDP1.5	Active Area	301.590 x 188.500 mm (typ)
	Dimensions (W x H)	307.590 x 199.550 mm (max)
	Weight	300 g (max)
	Diagonal Size	14 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	1200:1 (typ)
	Refresh Rate	60 Hz
	Brightness	400 nits (typ)
	Pixel Resolution	RGB
	Pixel Resolution - Format	1920x1200 (WUXGA)
	Aspect Ratio	16:10
	Backlight	WLED
	Color Gamut Coverage	sRGB 100%



Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption	EBL@200nits:1.40 W (Max) EBL@250nits:1.60 W (Max)



STORAGE

1 TB PCIe Gen5 NVMe™ Value 2280 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	1 TB
	NAND Type	Value
	Weight	10 g
	Interface	PCIe Gen5 NVMe
	Sequential Read	9500 MB/s ±20%
	Sequential Write	7000 MB/s ±20%
	Logical Blocks	2000409264
	Features	Pyrite 2.0; TRIM; L1.2 Not all features are available in all versions

1 TB PCIe® NVMe™ 2280 Self Encrypted OPAL2 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	1 TB
	NAND Type	Performance
	Weight	10 g
	Interface	PCIe Gen5x4 NVMe
	Sequential Read	13000 MB/s ±20%
	Sequential Write	9000 MB/s ±20%
	Logical Blocks	2000409264
	Features	TCG Opal 2.0; TRIM; L1.2 Not all features are available in all versions

1 TB PCIe® NVMe™ Value 2280 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	1TB
	NAND Type	Value
	Weight	10 g
	Interface	PCIe NVMe
	Sequential Read	3500 MB/s ±20%
	Sequential Write	2700 MB/s ±20%
	Logical Blocks	2000409264
	Features	Pyrite 2.0; TRIM; L1.2 Not all features are available in all versions



2 TB PCIe Gen5 NVMe™ Value 2280 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	2 TB
	NAND Type	Value
	Weight	10g
	Interface	PCIe Gen5 NVMe
	Sequential Read	10000 MB/s ±20%
	Sequential Write	8000 MB/s ±20%
	Logical Blocks	4000797360
	Features	Pyrite 2.0; TRIM; L1.2 Not all features are available in all versions

256 GB PCIe® NVMe™ Value 2280 Self Encrypted OPAL2 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	256 GB
	NAND Type	Value
	Weight	10g
	Interface	PCIe NVMe
	Sequential Read	3100 MB/s ±20%
	Sequential Write	1200 MB/s ±20%
	Logical Blocks	500118192
	Features	TCG Opal 2.0; TRIM; L1.2 Not all features are available in all versions

256 GB PCIe® NVMe™ Value 2280 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	256GB
	NAND Type	Value
	Weight	10 g
	Interface	PCIe NVMe
	Sequential Read	3100 MB/s ±20%
	Sequential Write	1200 MB/s ±20%
	Logical Blocks	500118192
	Features	Pyrite 2.0; TRIM; L1.2 Not all features are available in all versions



512 GB PCIe Gen5 NVMe™ Value 2280 Self Encrypted OPAL2 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	512 GB
	NAND Type	Value
	Weight	10 g
	Interface	PCIe Gen5 NVMe
	Sequential Read	9000 MB/s ±20%
	Sequential Write	6000 MB/s ±20%
	Logical Blocks	1000215216
	Features	TCG Opal 2.0; TRIM; L1.2

Not all features are available in all versions

512 GB PCIe Gen5 NVMe™ Value 2280 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	512 GB
	NAND Type	Value
	Weight	10g
	Interface	PCIe Gen5 NVMe
	Sequential Read	9000 MB/s ±20%
	Sequential Write	6000 MB/s ±20%
	Logical Blocks	1000215216
	Features	Pyrite 2.0; TRIM; L1.2

Not all features are available in all versions

512 GB PCIe® NVMe™ Value 2280 Solid State Drive ¹	Form Factor	M.2 2280
	Capacity	512GB
	NAND Type	Value
	Weight	10g
	Interface	PCIe NVMe
	Sequential Read	3500 MB/s ±20%
	Sequential Write	1600 MB/s ±20%
	Logical Blocks	1000215216
	Features	Pyrite 2.0; TRIM; L1.2

Not all features are available in all versions



1. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 32 GB is reserved for system recovery software.



NETWORKING / COMMUNICATION

Intel® AX211 Wi-Fi 6E

Wireless LAN Standards

IEEE 802.11a

Bluetooth® 5.3 WW WLAN^{1,2,3}

IEEE 802.11b

IEEE 802.11g

IEEE 802.11n

IEEE 802.11ac

IEEE 802.11ax

IEEE 802.11d

IEEE 802.11e

IEEE 802.11h

IEEE 802.11i

IEEE 802.11k

IEEE 802.11r

IEEE 802.11v

Interoperability

Wi-Fi certified

Frequency Band

802.11b/g/n/ax

2.402 - 2.482 GHz

802.11a/n/ac/ax

4.9 - 4.95 GHz (Japan)

5.15 - 5.25 GHz

5.25 - 5.35 GHz

5.47 - 5.725 GHz

5.825 - 5.850 GHz

5.955 - 6.415 GHz

6.435 - 6.515 GHz

6.535 - 6.875 GHz

6.895 - 7.115 GHz

Data Rates

802.11b: 1, 2, 5.5, 11 Mbps

802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11n: max 300Mbps

802.11ac: 1733Mbps

802.11ax: max 2.4Gbps



Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM , 1024QAM
Security	IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification IEEE 802.11i WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power	802.11b: +17dBm minimum 802.11g: +16dBm minimum 802.11a: +17dBm minimum 802.11n HT20(2.4GHz): +14dBm minimum 802.11n HT40(2.4GHz): +13dBm minimum 802.11n HT20(5GHz): +14dBm minimum 802.11n HT40(5GHz): +13dBm minimum 802.11ac VHT80(5GHz): +10dBm minimum 802.11ac VHT160(5GHz): +10dBm minimum 802.11ax HE40(2.4GHz): +12dBm minimum 802.11ax HE80(5GHz): +10dBm minimum 802.11ax HE160(5GHz): +10dBm minimum
Power Consumption	Transmit mode 2.0 W Receive mode 1.6 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode 50 mW (WLAN unassociated) Connected Standby 10mW



Power Management	Radio disabled 8 mW ACPI and PCI Express compliant power management
Receiver Sensitivity	802.11 compliant power saving mode 802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0(VHT80) : -84dBm maximum 802.11ac, MCS9(VHT80) : -59dBm maximum 802.11ac, MCS9(VHT160) : -58.5dBm maximum 802.11ax, MCS11(HE40) : -57dBm maximum 802.11ax, MCS11(HE80) : -54dBm maximum 802.11ax, MCS11(HE160) : -53.5dBm maximum
Antenna Type	High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm
Weight	1. Type 2230 : 2.8g
Operating Voltage	3.3v +/- 9%
Bluetooth® Specification	Integrated Bluetooth® specifications 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1



	<p>kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)</p>
Transmit Power	<p>The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.</p>
Power Consumption	<p>Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW</p>
Bluetooth® Software Supported Link Topology	<p>1. Microsoft Windows Bluetooth Software</p>
Power Management	<p>ACPI and PCI Express compliant power management 802.11 compliant power saving mode</p>
Certifications	<p>FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407</p>
Bluetooth® Profiles Supported	<p>ETSI 300 328, ETSI 301 893, ETSI 303 687 BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 -Link Layer Privacy LE Privacy 1.2 -Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2</p>



Intel® BE211 Wi-Fi 7
Bluetooth® 6.0 non-vPro WW
WLAN^{3,4}

Wireless LAN Standards

Interoperability
Frequency Band

ESR9/10 Compliance
LE Advertisement Extensions
Channel Selection Algo
Limited High Duty Cycle Non-Connectable Advertising
2Mbps LE
LE Long Range
BT5.3
Host to Controller Encryption Key Control Enhancements
Compliance to the latest Errata Section 12.3 of BT 5.3 specification
Periodic Advertisement interval

IEEE 802.11a
IEEE 802.11b
IEEE 802.11g
IEEE 802.11n
IEEE 802.11ac
IEEE 802.11ax
IEEE 802.11be
IEEE 802.11d
IEEE 802.11e
IEEE 802.11h
IEEE 802.11i
IEEE 802.11k
IEEE 802.11r
IEEE 802.11v
Wi-Fi certified
802.11b/g/n/ax/be
2.402 - 2.482 GHz
802.11a/n/ac/ax/be
5.15 - 5.25 GHz
5.25 - 5.35 GHz
5.47 - 5.725 GHz



	5.825 - 5.850 GHz
	5.955 - 6.415 GHz
	6.435 - 6.515 GHz
	6.535 - 6.875 GHz
	6.895 - 7.115 GHz
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps
	802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11n: max 300Mbps
	802.11ac: 1733Mbps
	802.11ax: max 2.4Gbps
	802.11be: max 5.76Gbps
Modulation	Direct Sequence Spread Spectrum
	OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM, 4096QAM
Security	WPA3 personal and enterprise including WPA2 transition mode.
	802.1X EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0-MSCHAPv2 (EAP-SIM, EAP-AKA, EAP-AKA')
	128-bit AES-CCMP, 256-bit AES-GCMP
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power	802.11b, 1Mbps: +17dBm minimum
	802.11g, 6Mbps: +16dBm minimum
	802.11a, 6Mbps: +17dBm minimum
	802.11n, MCS7(HT20): +14dBm minimum
	802.11n, MCS7(HT40): +13.5dBm minimum
	802.11ac MCS9(VHT20): 13.5dBm minimum
	802.11ac MCS9(VHT40): +13.5dBm minimum
	802.11ac MCS9(VHT80): +12.5dBm minimum
	802.11ac MCS9(VHT160): +10.5dBm minimum
	802.11ax MCS11(HE20)(6GHz): +11.5dBm minimum
	802.11ax MCS11(HE40)(6GHz): +7.5dBm minimum



	802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum
	802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum
	802.11be MCS13(EHT20)(6GHz) : +4dBm minimum
	802.11be MCS13(EHT40)(6GHz) : +7dBm minimum
	802.11be MCS13(EHT80)(6GHz) : +10dBm minimum
	802.11be MCS13(EHT160)(6GHz) : +13dBm minimum
	802.11be MCS13(EHT320)(6GHz) : +16dBm minimum
Power Consumption	Transmit mode 3.1 W
	Receive mode 1.8 W
	Idle mode (PSP) 180 mW (WLAN Associated)
	Idle mode 50 mW (WLAN unassociated)
	Connected Standby 10 mW
	Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management
	802.11 compliant power saving mode
Receiver Sensitivity	802.11b, 1Mbps : -93.5dBm maximum
	802.11b, 11Mbps : -85dBm maximum
	802.11a/g, 6Mbps : -90.5dBm maximum
	802.11a/g, 54Mbps : -72.5dBm maximum
	802.11n, MCS0(HT20) : -90dBm maximum
	802.11n, MCS7(HT20) : -71.5dBm maximum
	802.11n, MCS0(HT40) : -88.5dBm maximum
	802.11n, MCS7(HT40) : -68.5dBm maximum
	802.11ac, MCS9(VHT20) : -88.5dBm maximum
	802.11ac, MCS9(VHT40) : -65.5dBm maximum
	802.11ac, MCS9(VHT80) : -60.5dBm maximum
	802.11ac, MCS9(VHT160) : -58.5dBm maximum
	802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum
	802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum
	802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum
	802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum
	802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum
	802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum



Antenna Type	802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum 802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum 802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.99g 2. Type 1216: 0.72g
Operating Voltage	3.3v +/- 9%
Bluetooth® Specification	Integrated Bluetooth® specifications 4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4/6.0 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Bluetooth 4.x : 1Mbps (LE); 3Mbps (EDR) Bluetooth 5.x : 2Mbps (LE); 3Mbps (EDR) Bluetooth 6.0 : 2Mbps (LE); 3Mbps (EDR)
Transmit Power	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth® Software	1. Microsoft Windows Bluetooth Software
Supported Link Topology	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407



**Bluetooth® Profiles
Supported**

ETSI 300 328, ETSI 301 893, ETSI 303 687
 BT4.1-ESR 5/6/7 Compliance
 LE Link Layer Ping
 LE Dual Mode
 LE Link Layer
 LE Low Duty Cycle Directed Advertising
 LE L2CAP Connection Oriented Channels
 Train Nudging & Interlaced Scan
 BT4.2 ESR08 Compliance
 LE Secure Connection- Basic/Full
 LE Privacy 1.2 -Link Layer Privacy
 LE Privacy 1.2 -Extended Scanner Filter Policies
 LE Data Packet Length Extension
 FAX Profile (FAX)
 Basic Imaging Profile (BIP)2
 Headset Profile (HSP)
 Hands Free Profile (HFP)
 Advanced Audio Distribution Profile (A2DP)
 BT5.2
 ESR9/10 Compliance
 LE Advertisement Extensions
 Channel Selection Algo
 Limited High Duty Cycle Non-Connectable Advertising
 2Mbps LE
 LE Long Range
 BT5.3
 Host to Controller Encryption Key Control Enhancements
 Compliance to the latest Errata Section 12.3 of BT 5.3
 specification
 Periodic Advertisement interval

Intel® BE211 Wi-Fi 7

Wireless LAN Standards

IEEE 802.11a

Bluetooth® 6.0 vPro WW

IEEE 802.11b



WLAN^{3,4}

	IEEE 802.11g
	IEEE 802.11n
	IEEE 802.11ac
	IEEE 802.11ax
	IEEE 802.11be
	IEEE 802.11d
	IEEE 802.11e
	IEEE 802.11h
	IEEE 802.11i
	IEEE 802.11k
	IEEE 802.11r
	IEEE 802.11v
Interoperability	Wi-Fi certified
Frequency Band	802.11b/g/n/ax/be
	2.402 - 2.482 GHz
	802.11a/n/ac/ax/be
	5.15 - 5.25 GHz
	5.25 - 5.35 GHz
	5.47 - 5.725 GHz
	5.825 - 5.850 GHz
	5.955 - 6.415 GHz
	6.435 - 6.515 GHz
	6.535 - 6.875 GHz
	6.895 - 7.115 GHz
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps
	802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11n: max 300Mbps
	802.11ac: 1733Mbps
	802.11ax: max 2.4Gbps
	802.11be: max 5.76Gbps
Modulation	Direct Sequence Spread Spectrum
	OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM,



	1024QAM, 4096QAM
Security	WPA3 personal and enterprise including WPA2 transition mode. 802.1X EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0-MSCHAPv2 (EAP-SIM, EAP-AKA, EAP-AKA')
	128-bit AES-CCMP, 256-bit AES-GCMP
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power	802.11b, 1Mbps : +17dBm minimum 802.11g, 6Mbps : +16dBm minimum 802.11a, 6Mbps : +17dBm minimum 802.11n, MCS7(HT20) : +14dBm minimum 802.11n, MCS7(HT40) : +13.5dBm minimum 802.11ac MCS9(VHT20) : 13.5dBm minimum 802.11ac MCS9(VHT40) : +13.5dBm minimum 802.11ac MCS9(VHT80) : +12.5dBm minimum 802.11ac MCS9(VHT160) : +10.5dBm minimum 802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum 802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum 802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum 802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum 802.11be MCS13(EHT20)(6GHz) : +4dBm minimum 802.11be MCS13(EHT40)(6GHz) : +7dBm minimum 802.11be MCS13(EHT80)(6GHz) : +10dBm minimum 802.11be MCS13(EHT160)(6GHz) : +13dBm minimum 802.11be MCS13(EHT320)(6GHz) : +16dBm minimum
Power Consumption	Transmit mode 3.1 W Receive mode 1.8 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode 50 mW (WLAN unassociated) Connected Standby 10mW Radio disabled 8 mW



Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -85dBm maximum 802.11a/g, 6Mbps : -90.5dBm maximum 802.11a/g, 54Mbps : -72.5dBm maximum 802.11n, MCS0(HT20) : -90dBm maximum 802.11n, MCS7(HT20) : -71.5dBm maximum 802.11n, MCS0(HT40) : -88.5dBm maximum 802.11n, MCS7(HT40) : -68.5dBm maximum 802.11ac, MCS9(VHT20) : -88.5dBm maximum 802.11ac, MCS9(VHT40) : -65.5dBm maximum 802.11ac, MCS9(VHT80) : -60.5dBm maximum 802.11ac, MCS9(VHT160) : -58.5dBm maximum 802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum 802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum 802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum 802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum 802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum 802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum 802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum 802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum 802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum
Antenna Type	High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.99g 2. Type 1216: 0.72g



Operating Voltage	3.3v +/- 9%
Bluetooth® Specification	Integrated Bluetooth® specifications 4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4/6.0 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Bluetooth 4.x : 1Mbps (LE); 3Mbps (EDR) Bluetooth 5.x : 2Mbps (LE); 3Mbps (EDR) Bluetooth 6.0 : 2Mbps (LE); 3Mbps (EDR)
Transmit Power	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth® Software	1.Microsoft Windows Bluetooth Software
Supported Link Topology	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407 ETSI 300 328, ETSI 301 893, ETSI 303 687
Bluetooth® Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 -Link Layer Privacy LE Privacy 1.2 -Extended Scanner Filter Policies



LE Data Packet Length Extension
 FAX Profile (FAX)
 Basic Imaging Profile (BIP)2
 Headset Profile (HSP)
 Hands Free Profile (HFP)
 Advanced Audio Distribution Profile (A2DP)
 BT5.2
 ESR9/10 Compliance
 LE Advertisement Extensions
 Channel Selection Algo
 Limited High Duty Cycle Non-Connectable Advertising
 2Mbps LE
 LE Long Range
 BT5.3
 Host to Controller Encryption Key Control Enhancements
 Compliance to the latest Errata Section 12.3 of BT 5.3
 specification
 Periodic Advertisement interval

HP 5G NR Sub-6 CAT19⁵

Technology Operating Bands

WCDMA/HSPA+ operating bands:
 Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
 Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
 Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)
 Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
 Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)

LTE FDD/TDD operating bands:
 Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
 Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
 Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)
 Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)
 Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
 Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)
 Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)



Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)
Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL)
Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)
Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL)
Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL)
Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL)
Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)
Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)
Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)
Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)
Band 29: 717 to 728 MHz (DL)
Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)
Band 32: 1452 to 1496 MHz (DL)
Band 34: 2010 to 2025 MHz (UL/DL)
Band 38: 2570 to 2620 MHz (UL/DL)
Band 39: 1880 to 1920 MHz (UL/DL)
Band 40: 2300 to 2400 MHz (UL/DL)
Band 41: 2496 to 2690 MHz (UL/DL)
Band 42: 3400 to 3600 MHz (UL/DL)
Band 43: 3400 to 3800 MHz (UL/DL)
Band 46: 5150 to 5925 MHz (DL)
Band 48: 3550 to 3700 MHz (UL/DL)
Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)
Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)
5G NR Sub 6GHz
n1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
n2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
n3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)
n5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
n7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)
n8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)
n12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)
n14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)



n20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)
 n25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)
 n26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)
 n28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)
 n30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)
 n38: 2570 to 2620 MHz (UL/DL)
 n40: 2300 to 2400 MHz (UL/DL)
 n41: 2496 to 2690 MHz (UL/DL)
 n48: 3550 to 3700 MHz (UL/DL)
 n66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)
 n71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)
 n77: 3300 to 4200 MHz (UL/DL)
 n78: 3300 to 3800 MHz (UL/DL)
 n79: 4400 to 5000 MHz (UL/DL)

Wireless Protocol Standards

NR Sub6G rel15
 200MHz 2 DLCA, 256 QAM
 200MHz 2 ULCA, 256 QAM
 15KHz/30KHz SCS for FDD/TDD
 LTE Rel15
 100MHz 5 DLCA, 256 QAM
 40MHz 2 ULCA, 256 QAM
 UMTS Rel8

GPS

GPS only support L1 C/A

GPS Bands

GPS: L1 (1575.42MHz)
 GLONASS: L1 (1602MHz)
 BeidouB1(1561.098MHz)
 Galileo E1 (1575.42)
 QZSS(1575.42 MHz)

Maximum Data Rates

Sub-6 SA Peak
 DL 4.67Gbps/UL 1.25Gbps
 Sub-6 NSA Peak
 DL 3.74Gbps/UL 835Mbps
 LTE Peak



	DL 1.6Gbps (CAT19)/UL 211Mbps (CAT18)
	UMTS/HSPA+
	DL DC-HSPA+: 42 Mbps (CAT24)/UL 11.5 Mbps (CAT7)
Maximum Output Power	NR :
	23 dBm in all band except (n30 = 22dBm & n48=21dBm & n77=25dBm & n41/n77/n78 = 26dBm)
	LTE:
	23 dBm in all band except (B30 = 22dBm & B48=21dBm & B41=26dBm)
	UMTS:
	23.5 dBm
Maximum Power Consumption	3500 mA (peak); 1674mA (average)
Form Factor	M.2, 3052-S3 Key B
Weight	8.7g
Dimensions (Length x Width x Thickness)	52 mm × 30 mm × 2.3 mm
Embedded eSIM	Support

HP 5G NR Sub-6 CAT19 HP Go Solution⁵

Technology Operating Bands	WCDMA/HSPA+ operating bands:
	Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
	Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
	Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)
	Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
	Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)
	LTE FDD/TDD operating bands:
	Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
	Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
	Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)
	Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)
	Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
	Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)
	Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)



Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)
Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL)
Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)
Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL)
Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL)
Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL)
Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)
Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)
Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)
Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)
Band 29: 717 to 728 MHz (DL)
Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)
Band 32: 1452 to 1496 MHz (DL)
Band 34: 2010 to 2025 MHz (UL/DL)
Band 38: 2570 to 2620 MHz (UL/DL)
Band 39: 1880 to 1920 MHz (UL/DL)
Band 40: 2300 to 2400 MHz (UL/DL)
Band 41: 2496 to 2690 MHz (UL/DL)
Band 42: 3400 to 3600 MHz (UL/DL)
Band 43: 3400 to 3800 MHz (UL/DL)
Band 46: 5150 to 5925 MHz (DL)
Band 48: 3550 to 3700 MHz (UL/DL)
Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)
Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)
5G NR Sub 6GHz
n1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
n2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
n3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)
n5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
n7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)
n8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)
n12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)
n14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)



n20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)
 n25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)
 n26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)
 n28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)
 n30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)
 n38: 2570 to 2620 MHz (UL/DL)
 n40: 2300 to 2400 MHz (UL/DL)
 n41: 2496 to 2690 MHz (UL/DL)
 n48: 3550 to 3700 MHz (UL/DL)
 n66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)
 n71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)
 n77: 3300 to 4200 MHz (UL/DL)
 n78: 3300 to 3800 MHz (UL/DL)
 n79: 4400 to 5000 MHz (UL/DL)

Wireless Protocol Standards

NR Sub6G rel15
 200MHz 2 DLCA, 256 QAM
 200MHz 2 ULCA, 256 QAM
 15KHz/30KHz SCS for FDD/TDD
 LTE Rel15
 100MHz 5 DLCA, 256 QAM
 40MHz 2 ULCA, 256 QAM
 UMTS Rel8

GPS

GPS only support L1 C/A

GPS Bands

GPS: L1 (1575.42MHz)
 GLONASS: L1 (1602MHz)
 BeidouB1(1561.098MHz)
 Galileo E1 (1575.42)
 QZSS(1575.42 MHz)

Maximum Data Rates

Sub-6 SA Peak
 DL 4.67Gbps/UL 1.25Gbps
 Sub-6 NSA Peak
 DL 3.74Gbps/UL 835Mbps
 LTE Peak



	DL 1.6Gbps (CAT19)/UL 211Mbps (CAT18)
	UMTS/HSPA+
	DL DC-HSPA+: 42 Mbps (CAT24)/UL 11.5 Mbps (CAT7)
Maximum Output Power	NR :
	23 dBm in all band except (n30 = 22dBm & n48=21dBm & n77=25dBm & n41/n77/n78 = 26dBm)
	LTE:
	23 dBm in all band except (B30 = 22dBm & B48=21dBm & B41=26dBm)
	UMTS:
	23.5 dBm
Maximum Power Consumption	3500 mA (peak); 1674mA (average)
Form Factor	M.2, 3052-S3 Key B
Weight	8.7g
Dimensions (Length x Width x Thickness)	52 mm × 30 mm × 2.3 mm
Embedded eSIM	Support

NFC Mirage WNC XR4V-1	Dimensions (L x W x H)	17.00 x 10.00 x 2.00 mm (0.67 x 0.39 x 0.08 inch)
	Chipset	NPC300
	System Interface	I2C
	NFC RF Standards	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
	NFC Forum Support	Type 1, Type 2, Type 3 / Type 4, NFCIP-1 / NFCIP-2



Reader Mode (PCD-VCD)	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz
Card Emulation Mode (PICC-VICC)	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
Frequency	13.56 MHz
NFC Modes Supported	Reader/Writer, Peer-to-Peer
Raw RF Data Rates	106 kbps, 212 kbps, 424 kbps, 848 kbps
Operating Temperature	0°C to 70°C (32°F to 158°F)
Storage Temperature	125°C to 125°C (-4°F to 257°F)
Humidity	Operating: 10 - 90% Non-Operating: 5 - 95%
Supply Operating Voltage	4.35 to 5.25 Volts
I/O Voltage	1.8V or 3.3V
Power Consumption Mode	Booster enable, VBAT= 3.3V, VCC_BOOST = 5V
Polling	Power Consumption, Typical 7.3 mA
Detected Test Tag Type 1	Total 283.8 mA Net Module 236.8 mA
Detected Test Tag Type 2	Total 288.8 mA Net Module 241.8 mA



Detected Test Tag Type 3	Total 287.7 mA Net Module 240.7 mA
Detected Test Tag Type 4	Total 282.3 mA Net Module 235.3 mA
Antenna	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.
Intel® I219-LM 1GbE Vpro Ethernet Controller	<p>Connector RJ-45</p> <p>System Interface PCI(Intel proprietary) + SMBus</p> <p>Data Rates Supported 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s</p> <p>IEEE Compliance IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet)</p> <p>Performance TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling(Hash Mode Only) Jumbo Frame 9K</p> <p>Power Consumption Cable Disconnection: 25mW 100Mbps Full Run: 450mW 1000bp Full Run: 1000mW WoL Enable(S3/S4/S5): 50mW WoL Disable(S3/S4/S5): 25mW</p>



Power Management	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption								
Management Interface	Auto MDI/MDIX Crossover cable detection								
IT Manageability	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status								
Security & Manageability	Intel® vPro™ support with appropriate Intel® chipset components								
Intel® I219-V 1GbE Ethernet Controller	<table border="0"> <tr> <td style="vertical-align: top;">Connector</td> <td>RJ-45</td> </tr> <tr> <td style="vertical-align: top;">System Interface</td> <td>PCI(Intel proprietary) + SMBus</td> </tr> <tr> <td style="vertical-align: top;">Data Rates Supported</td> <td> <ol style="list-style-type: none"> 1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) 4. Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10, 100 & 1000 Mbit/s </td> </tr> <tr> <td style="vertical-align: top;">IEEE Compliance</td> <td> IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX </td> </tr> </table>	Connector	RJ-45	System Interface	PCI(Intel proprietary) + SMBus	Data Rates Supported	<ol style="list-style-type: none"> 1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) 4. Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10, 100 & 1000 Mbit/s	IEEE Compliance	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX
Connector	RJ-45								
System Interface	PCI(Intel proprietary) + SMBus								
Data Rates Supported	<ol style="list-style-type: none"> 1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) 4. Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10, 100 & 1000 Mbit/s								
IEEE Compliance	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX								



		IEEE 802.3ab 1000BASE-T
		IEEE 802.3bz 2.5GBASE-T
Performance		TCP/IP/UDP Checksum Offload (configurable)
		Protocol Offload (ARP & NS)
		Large send offload and Giant send offload
		Receiving Side Scaling(Hash Mode only)
		Jumbo Frame 9K
Power Consumption		Cable Disconnection: 25mW
		100Mbps Full Run: 450mW
		1000bps Full Run: 1000mW
		WoL Enable(S3/S4/S5): 50mW
		WoL Disable(S3/S4/S5): 25mW
Power Management		ACPI compliant - multiple power modes
		Situation-sensitive features reduce power consumption
		Advanced link down power saving for reducing link down power consumption
Management Interface		Auto MDI/MDIX Crossover cable detection
IT Manageability		Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)
		PXE 2.1 Remote Boot
		Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))
		Comprehensive diagnostic and configuration software suite
		Virtual Cable Doctor for Ethernet cable status
Security & Manageability		Intel® non-vPro™ support with appropriate Intel® chipset components
HP RW220-GL LTE (Low Power) (CAT-1bis)	Technology/Operating bands	FDD LTE: 2100 (Band 1), 1800 (Band 3), 850 (Band 5), 900 (Band 8), 700 (Band 12), 850 (Band 18), 850 (Band 19), 800 (Band 20), 850 (Band 26), 700 (Band 28)
		WIFI Scan : 802.11b
	Wireless Protocol Standards	3GPP TS 51.010-1 V12.9.0: Mobile Station (MS) conformance



	<p>specification; Part 1: Conformance specification</p> <p>3GPP TS 36.521-1 V13.3.0: User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing</p> <p>3GPP TS 21.111 V10.0.0: USIM and IC card requirements</p> <p>3GPP TS 51.011 V4.15.0: Specification of the Subscriber Identity Module -Mobile Equipment (SIM-ME) interface</p> <p>3GPP TS 31.102 V10.11.0: Characteristics of the Universal Subscriber Identity Module (USIM) application</p> <p>3GPP TS 31.111 V10.16.0: Universal Subscriber Identity Module (USIM) Application Toolkit (USAT)</p> <p>3GPP TS 36.124 V13.2.0: Electro Magnetic Compatibility (EMC) requirements for mobile terminals and ancillary equipment</p> <p>3GPP TS 27.007 V10.0.8: AT command set for User Equipment (UE)</p> <p>3GPP TS 27.005 V10.0.1: Use of Data Terminal Equipment - Data Circuit terminating Equipment (DTE DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (CBS)</p>
GPS	<p>GPS, Galileo, BeiDou, QZSS, AGPS-MS-B</p>
GPS Bands	<p>GPS L1:1575.42Mhz±1.023Mhz, BDS B1:1561.098Mhz±2.046Mhz , Galileo E1:1575.42Mhz±1.023Mhz , QZSS L1:1575.42Mhz±1.023Mhz</p>
Maximum Data Rates	<p>Downlink: 10Mbps</p> <p>Uplink: 5Mbps</p>
Maximum Output Power	<p>B1/3: 23 +/-2dBm, B5/8/12/18/19/20/26/28: 24 +1.7/-2dBm</p>



Maximum Power Consumption	<p>S0 USB suspend: Peak Current : 290.945mA Typical average current : 8.035mA</p> <p>S5 USB suspend & USB disable: Peak Current : 291.185mA Typical average current : 2.723mA</p>
Form Factor	M.2
Weight	3.9g
Dimensions (Length x Width x Thickness)	42.0 mm × 22.0 mm × 2.3 mm
Embedded eSIM	Support

HP RW220-GL LTE (Low Power) (CAT-1bis) with GPS

Technology/Operating bands	<p>FDD LTE: 2100 (Band 1), 1800 (Band 3), 850 (Band 5), 900 (Band 8), 700 (Band 12), 850 (Band 18), 850 (Band 19), 800 (Band 20), 850 (Band 26), 700 (Band 28)</p> <p>WIFI Scan : 802.11b</p>
Wireless Protocol Standards	<p>-3GPP TS 51.010-1 V12.9.0: Mobile Station (MS) conformance specification; Part 1: Conformance specification</p> <p>-3GPP TS 36.521-1 V13.3.0: User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing</p> <p>-3GPP TS 21.111 V10.0.0: USIM and IC card requirements</p> <p>-3GPP TS 51.011 V4.15.0: Specification of the Subscriber Identity Module -Mobile Equipment (SIM-ME) interface</p> <p>-3GPP TS 31.102 V10.11.0: Characteristics of the Universal Subscriber Identity Module (USIM) application</p> <p>-3GPP TS 31.111 V10.16.0: Universal Subscriber Identity Module (USIM) Application Toolkit (USAT)</p> <p>-3GPP TS 36.124 V13.2.0: Electro Magnetic Compatibility (EMC) requirements for mobile terminals and</p>



	ancillary equipment
	-3GPP TS 27.007 V10.0.8: AT command set for User Equipment (UE)
	-3GPP TS 27.005 V10.0.1: Use of Data Terminal Equipment - Data Circuit terminating Equipment (DTE DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (CBS)
GPS	GPS, Galileo, BeiDou, QZSS, AGPS-MS-B
GPS Bands	GPS L1:1575.42Mhz±1.023Mhz, BDS B1:1561.098Mhz±2.046Mhz , Galileo E1:1575.42Mhz±1.023Mhz , QZSS L1:1575.42Mhz±1.023Mhz
Maximum Data Rates	Downlink: 10Mbps Uplink: 5Mbps
Maximum Output Power	B1/3: 23 +/-2dBm, B5/8/12/18/19/20/26/28: 24 +1.7/-2dBm
Maximum Power Consumption	S0 USB suspend: Peak Current : 290.945mA Typical average current : 8.035mA S5 USB suspend & USB disable: Peak Current : 291.185mA Typical average current : 2.723mA
Form Factor	M.2
Weight	3.9g
Dimensions (Length x Width x Thickness)	42.0 mm × 22.0 mm × 2.3 mm
Embedded eSIM	Support

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.
2. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately.



3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

4. Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

5. 5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier supported.



POWER

Power supply availability may vary by country.

100W GaN USB-C AC power adapter	Weight (DC Cable Included)	106 g ± 10 g
	Input	100 Vac ~ 240 Vac
	Input Efficiency	USB-C
		90.00 % min at 115 Vac/ 230 Vac @ 20.00 V/ 5.00 A
	Input frequency range	47 Hz ~ 63 Hz
	Input AC current	Max 1.60 A at 90 Vac input
	Output	
	Output power	20.00 V / 100.00 W
	DC output	+ 20.00 V
	Hold - up time	5 ms at 115 Vac input
	Output Over Current	5.40 A (max)
	Protection	
	AC Inlet Type	Fixed 2 Prong
	DC Cable Connector	USB Type-C
	DC Cable Material	Halogen Free
	Connector	
	Connector	Fixed 2 Prong
	DC Plug	USB Type-C
	Environmental Design	
	Operating temperature	0°C to 35°C (32°F to 95°F)
	Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
	Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
Humidity	20 % to 95 %	
Storage Humidity	10 % to 95 %	
EML and Safety Certifications	Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE,	



NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

100W GaN USB-C AC power adapter

Weight (DC Cable Included)	250 g ± 10 g
Input	100 Vac ~ 240 Vac
Input Efficiency	USB-C
	90.00 % min at 115 Vac/ 230 Vac @ 20.00 V/ 5.00 A
Input frequency range	47 Hz ~ 63 Hz
Input AC current	Max 1.60 A at 90 Vac input
Output	
Output power	20.00 V / 100.00 W
DC output	+ 20.00 V
Hold - up time	5 ms at 115 Vac input
Output Over Current	5.40 A (max)
Protection	
AC Inlet Type	Foldable for 2 prong
DC Cable Connector	USB Type-C
DC Cable Material	Halogen Free
Connector	
Connector	Foldable for 2 prong
DC Plug	USB Type-C
Environmental Design	
Operating temperature	0°C to 35°C (32°F to 95°F)
Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
Humidity	20 % to 95 %
Storage Humidity	10 % to 95 %
EMI and Safety Certifications	Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE,



NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

65W GaN USB-C AC power adapter

Weight (DC Cable Included)	185 g ± 10 g
Input	100 Vac ~ 240 Vac
Input Efficiency	USB-C
	89.00 % min at 115 Vac/ 230 Vac @ 20.00 V/ 3.25 A
Input frequency range	47 Hz ~ 63 Hz
Input AC current	Max 1.60 A at 90 Vac input
Output	
Output power	20.00 V / 65.00 W
DC output	+ 20.00 V
Hold - up time	5 ms at 115 Vac input
Output Over Current	5.40 A (max)
Protection	
AC Inlet Type	C6
DC Cable Connector	USB Type-C
DC Cable Material	Low Halogen
Connector	
Connector	C6
DC Plug	USB Type-C
Environmental Design	
Operating temperature	0°C to 35°C (32°F to 95°F)
Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
Humidity	20 % to 95 %
Storage Humidity	10 % to 95 %
EMI and Safety Certifications	Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE,



NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

65W GaN USB-C AC power adapter

Weight (DC Cable Included)	185 g ± 10 g
Input	100 Vac ~ 240 Vac
Input Efficiency	USB-C 89.00 % min at 115 Vac/ 230 Vac @ 20.00 V/ 3.25 A
Input frequency range	47 Hz ~ 63 Hz
Input AC current	Max 1.60 A at 90 Vac input
Output	
Output power	20.00 V / 65.00 W
DC output	+ 20.00 V
Hold - up time	5 ms at 115 Vac input
Output Over Current	5.40 A (max)
Protection	
AC Inlet Type	Foldable for 2 prong
DC Cable Connector	USB Type-C
DC Cable Material	Halogen Free
Connector	
Connector	Foldable for 2 prong
DC Plug	USB Type-C
Environmental Design	
Operating temperature	0°C to 35°C (32°F to 95°F)
Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
Humidity	20 % to 95 %
Storage Humidity	10 % to 95 %
EMI and Safety Certifications	Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE,



NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

65W GaN USB-C AC power adapter

Weight (DC Cable Included)	185 g ± 10 g
Input	100 Vac ~ 240 Vac
Input Efficiency	USB-C 89.00 % min at 115 Vac/ 230 Vac @ 20.00 V/ 3.25 A
Input frequency range	47 Hz ~ 63 Hz
Input AC current	Max 1.60 A at 90 Vac input
Output	
Output power	20.00 V / 65.00 W
DC output	+ 20.00 V
Hold - up time	5 ms at 115 Vac input
Output Over Current	5.50 A (max)
Protection	
AC Inlet Type	Fixed 2 Prong
DC Cable Connector	USB Type-C
DC Cable Material	Halogen Free
Connector	
Connector	Fixed 2 Prong
DC Plug	USB Type-C
Environmental Design	
Operating temperature	0°C to 35°C (32°F to 95°F)
Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
Humidity	20 % to 95 %
Storage Humidity	10 % to 95 %
EMI and Safety Certifications	Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC),



EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

HP 140W Slim USB-C AC power adapter

Weight (DC Cable Included)	420 g ± 10 g
Input	100 Vac ~ 240 Vac
Input Efficiency	USB-C
	90.00 % min at 115 Vac/ 230 Vac @ 28.00 V/ 5.00 A
Input frequency range	47 Hz ~ 63 Hz
Input AC current	Max 2.50 A at 90 Vac input
Output	
Output power	28.00 V / 140.00 W
DC output	+ 28.00 V
Hold - up time	5 ms at 115 Vac input
Output Over Current	5.40 A (max)
Protection	
AC Inlet Type	C6
DC Cable Connector	USB Type-C
DC Cable Material	Low Halogen
Connector	
Connector	C6
DC Plug	USB Type-C
Environmental Design	
Operating temperature	0°C to 35°C (32°F to 95°F)
Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
Humidity	20 % to 95 %
Storage Humidity	10 % to 95 %
EMI and Safety Certifications	Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC),



EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

Battery

Battery is internal and replaceable by customer. Serviceable by warranty.

MC 68Wh Long Life Polymer Fast charge 3 cell Battery	<p>Weight 251 g ± 10 g (1.55 lb)</p> <p>Cells / Type 3 cell Lithium-Ion Polymer /</p> <p>Energy</p> <p>Voltage 11.67 V</p> <p>Amp - hour capacity 5.830 Ah</p> <p>Watt - hour capacity 68Wh.000 Wh</p> <p>Temperature</p> <p>Operating (Charging) 0°C to 45°C (32°F to 113°F)</p> <p>Operating (Discharging) -10°C to 65°C (14°F to 149°F)</p> <p>Optional Travel Battery No</p> <p>Available</p>
MW 77Whr Long Life Polymer Fast charge 8 cell Battery	<p>Weight 292 g ± 10 g (1.64 lb)</p> <p>Cells / Type 8 cell Lithium-Ion Polymer / 406553</p> <p>Energy</p> <p>Voltage 15.44 V</p> <p>Amp - hour capacity 4.988 Ah</p> <p>Watt - hour capacity 77Wh.000 Wh</p> <p>Temperature</p> <p>Operating (Charging) 0°C to 45°C (32°F to 113°F)</p> <p>Operating (Discharging) -10°C to 65°C (14°F to 149°F)</p> <p>Optional Travel Battery No</p> <p>Available</p>



AUDIO

Privacy panel is only available on select models.

Codec	Realtec ALC3315-CG
Audio I/O Ports	3.5mm Headset: CTIA only; Headset: CTIA only
Internal Speaker Amplifier	TI TAS2783A 23-V Soundwire Mono Smart Amplifier
Multi-streaming Capable	Playback multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the front jacks or integrated speaker.
Sampling	DAC: Supports resolutions from 16-bit to 24-bit;48.0 kHz to 48.0 kHz ADC: Supports resolutions from 16-bit to 24-bit;44.1 kHz to 48.0 kHz
Internal Speaker	Yes



FINGERPRINT READER

Sensor vendor	SYNAPTICS
Sensor type	Capacitive
DPI resolution	363 DPI
Scan area	104 x 86 pixels
False Rejection Rate	< 3%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	2.7 V ~ 3.6 V
Operating Temperature	5°C ~ 60°C (41°F ~ 140°F)
Current Consumption Image	100 mA max
Low Latency Wait For Finger	260 uA
Capture Rate	50 frames/sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	363 dpi / 7.4 x 6.0 mm sensor area

Sensor vendor	ELAN
Sensor type	Capacitive
DPI resolution	363 DPI
Scan area	56 x 56 pixels
False Rejection Rate	< 3%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	2.8 V ~ 3.6 V
Operating Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Current Consumption Image	100 mA max
Low Latency Wait For Finger	300 uA
Capture Rate	50 frames/sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	363 dpi / 4.0 x 4.0 mm sensor area

Sensor vendor	Goodix
Sensor type	Capacitive
DPI resolution	500 DPI



Scan area	176x 54 pixels
False Rejection Rate	<2%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	2.8 V ~ 3.6 V
Operating Temperature	-40°C~125°C(-40°F ~ 257°F)
Current Consumption Image	34.2mA
Low Latency Wait For Finger	360 uA
Capture Rate	50 frames/sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	500 dpi / 8.9 x 2.7 mm sensor area



OPTIONS

Container Name	Description	Part Number
Adapters	HP 240W Thunderbolt 4 Cable	BR1W8AA
	HP HDMI to VGA Adapter	H4F02AA,H4F02UT
	HP USB 3.0 to Gigabit RJ45 Adapter G2	4Z7Z7AA,4Z7Z7UT
	HP USB-C to DisplayPort Adapter G2	8Y8Y1AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA,1WC36UT
	HP USB-C to RJ45 Adapter G2	4Z527AA,4Z527UT
	HP USB-C to USB 3.0 Adapter	N2Z63AA,N2Z63UT
	HP USB-C to VGA Adapter	N9K76AA,N9K76UT
Audio - Earbuds	Poly Voyager Free 60+ Carbon Black Earbuds	7Y8G4AA
	Poly Voyager Free 60+ Carbon Black Earbuds	7Y8H0AA
Audio - Headset	HP USB G2 Stereo Headset	428K6AA,428K6UT
	Poly Blackwire 3210 Monaural USB-C Headset	8X214AA
	Poly Blackwire 3215 Monaural USB-C Headset	8X227AA
	Poly Blackwire 3220 Stereo USB-C Headset	8X228AA
	Poly Blackwire 3225 Stereo USB-C Headset	8X229AA
	Poly Blackwire 3310 Monaural USB-C Headset	8X215AA
	Poly Blackwire 3310 Monaural USB-C Headset	8X216AA
	Poly Blackwire 3315 Monaural USB-C Headset	8X217AA
	Poly Blackwire 3315 Monaural USB-C Headset	8X218AA
	Poly Blackwire 3320 Stereo USB-C Headset	8X219AA
	Poly Blackwire 3320 Stereo USB-C Headset	8X220AA
	Poly Blackwire 3325 Stereo USB-C Headset	8X221AA
	Poly Blackwire 3325 Stereo USB-C Headset	8X222AA
	Poly Blackwire 5210 Monaural USB-C Headset	8X230AA
	Poly Blackwire 5220 Stereo USB-C Headset	8X231AA
	Poly Blackwire 8225 Stereo USB-C Headset	8X223AA
	Poly Blackwire 8225 Stereo USB-C Headset	8X225AA
	Poly EncorePro 320 Binaural Headset	77T26AA
	Poly EncorePro 510 Monaural Headset	783Q2AA
	Poly EncorePro 510 Monoaural Headset	783Q1AA



Poly EncorePro 520 Binaural Headset	783P6AA
Poly EncorePro 520 Binaural Headset	783P7AA
Poly EncorePro 530 Discreet Headset	783P2AA
Poly EncorePro 530 Headset	783P3AA
Poly EncorePro 540 Convertible Headset	783P0AA
Poly EncorePro 540 Convertible Headset	783P1AA
Poly EncorePro 720 Binaural Headset	8R707AA
Poly EncorePro HW710 Single Ear Headset	8R708AA
Poly EncorePro Monoaural 310 Headset	77T43AA
Poly EncorePro Monoaural 515 with USB-A Headset	783R0AA
Poly EncorePro Monoaural 515 with USB-A Headset	783R1AA
Poly EncorePro Stereo 525 with USB-A Headset	783R2AA
Poly EncorePro USB-A Monoaural 715 Headset	783N5AA
Poly EncorePro USB-A Stereo 525 Headset	783R3AA
Poly EncorePro USB-A Stereo 725 Headset	783M6AA
Poly EncorePro USB-C Monoaural 310 Headset	760Q8AA
Poly Savi 7310 DECT 1880-1900 MHz Single Ear Headset	8D3G3AA
Poly Savi 7310 Monoaural DECT 1880-1900 MHz Headset	8L561AA
Poly Savi 7310 Monoaural DECT 1880-1900 MHz Headset	8L575AA
Poly Savi 7310 Monoaural DECT 1920-1930 MHz Headset	7S430AA
Poly Savi 7310 Monoaural DECT 1920-1930 MHz Headset	8L570AA
Poly Savi 7310 Monoaural DECT 1920-1930 MHz Headset	8L585AA
Poly Savi 7310-M DECT 1880-1900 MHz Single Ear Headset	8D3K7AA
Poly Savi 7310-M DECT 1920-1930 MHz Single Ear Headset	7S439AA
Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset	8D3F7AA
Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset	8L545AA
Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset	8L553AA
Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset	8D3F8AA
Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset	8L546AA
Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset	8L555AA
Poly Savi 7320 Stereo DECT 1910-1920 MHz Headset	8D3G0AA
Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset	7S429AA
Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset	8L549AA



Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset	8L559AA
Poly Savi 7320-M Stereo DECT 1880-1900 MHz Headset	8D3J6AA
Poly Savi 7320-M Stereo DECT 1893-1906 MHz Headset	8D3K2AA
Poly Savi 7320-M Stereo DECT 1910-1920 MHz Headset	8D3K0AA
Poly Savi 7320-M Stereo DECT 1920-1930 MHz Headset	7S435AA
Poly Savi 8210 DECT 1880-1900 MHz USB-A Headset	8D3E9AA
Poly Savi 8210 DECT 1880-1900 MHz USB-A Headset	8D3F1AA
Poly Savi 8210 DECT 1920-1930 MHz USB-A Headset	77T29AA
Poly Savi 8210 DECT 1920-1930 MHz USB-A Headset	77T31AA
Poly Savi 8220 DECT 1880-1900 MHz USB-A Headset	8D3F2AA
Poly Savi 8220 DECT 1880-1900 MHz USB-A Headset	8D3F5AA
Poly Savi 8220 DECT 1920-1930 MHz USB-A Headset	77T33AA
Poly Savi 8220 DECT 1920-1930 MHz USB-A Headset	77Y82AA
Poly Savi 8220 Stereo DECT 1880-1900 MHz Top	8Y9C4AA
Poly Savi 8245 DECT 1880-1900 MHz Headset	8D3H2AA
Poly Savi 8245 DECT 1880-1900 MHz USB-A Headset	8D3F4AA
Poly Savi 8410 Monaural DECT 1880-1900 MHz Headset	8L5A7AA
Poly Savi 8410 Monaural DECT 1880-1900 MHz Headset	8L5A9AA
Poly Savi 8410 Monaural DECT 1920-1930 MHz Headset	8L7E6AA
Poly Savi 8410 Monaural DECT 1920-1930 MHz Headset	8L7E9AA
Poly Savi 8420 Stereo DECT 1880-1900 MHz Headset	8L5B2AA
Poly Savi 8420 Stereo DECT 1880-1900 MHz Headset	8L5B3AA
Poly Savi 8420 Stereo DECT 1920-1930 MHz Headset	8L7F2AA
Poly Savi 8420 Stereo DECT 1920-1930 MHz Headset	8L7F5AA
Poly Savi 8445 DECT 1880-1900 MHz Convertible Headset	8L5B4AA
Poly Savi 8445 DECT 1880-1900 MHz Convertible Headset	8L5B6AA
Poly Savi 8445 DECT 1920-1930 MHz Convertible Headset	8L7F1AA
Poly Savi 8445 DECT 1920-1930 MHz Convertible Headset	8L7F8AA
Poly Voyager 4310 Headset	77Y93AA
Poly Voyager 4310 Monaural Headset	77Y92AA
Poly Voyager 4310 USB-A Headset	76U48AA
Poly Voyager 4310 USB-A Headset	77Y91AA
Poly Voyager 4310 USB-C Headset	77Y94AA



	Poly Voyager 4310 USB-C Headset	77Y95AA
	Poly Voyager 4310 USB-C Headset	77Y96AA
	Poly Voyager 4310-M USB-C Headset	77Y97AA
	Poly Voyager 4320 Headset	77Z00AA
	Poly Voyager 4320 Stereo USB-A Headset	77Y99AA
	Poly Voyager 4320 USB-A Headset	76U49AA
	Poly Voyager 4320 USB-A Headset	77Y98AA
	Poly Voyager 4320 USB-C Headset	76U50AA
	Poly Voyager 4320 USB-C Headset	77Z30AA
	Poly Voyager 4320 USB-C Headset	77Z31AA
	Poly Voyager 4320-M Headset	77Z32AA
	Poly Voyager Focus 2 USB-C-C Headset	9T9J3AA
	Poly Voyager Focus 2 USB-C-C Headset	9T9J5AA
	Poly Voyager Focus 2 USB-C-C Headset	9T9J6AA
	Poly Voyager Legend 50 Headset UC	AT9M9AA,AT9M9UT
	Poly Voyager Legend 50-M Headset UC	AJ8V4AA,AJ8V4UT
	Poly Voyager Surround 80 USB-C Headset	8G7T9AA
	Poly Voyager Surround 80 USB-C Headset	8G7U0AA
	Poly Voyager Surround 85 USB-C Headset	8G7T7AA
	Poly Voyager Surround 85 USB-C Headset	8G7T8AA
Audio - Speaker phone	Poly Sync 10 Speakerphone	77P34AA
	Poly Sync 20 Speakerphone USB-C/A Adapter	B95VJUT
	Poly Sync 20+ Speakerphone	B95VKAA
	Poly Sync 20+M Speakerphone USB-C/A Adapter	B95VLAA
	Poly Sync 20-M Speakerphone USB-C/A Adapter	B95VMUT
	Poly Sync 40 Speakerphone	77P35AA
	Poly Sync 40+ USB-A USB-C Speakerphone	77P36AA
	Poly Sync 40+ USB-A USB-C Speakerphone	772C5AA
	Poly Sync 60 Speakerphone	772C2AA
	Poly Sync 60 Speakerphone	77P41AA
	Poly Sync USB-A USB-C 10 Speakerphone	772C3AA
	Poly Sync USB-A USB-C 40 Speakerphone	772C4AA
	Camera	HP 625 Webcam



Cases

HP USB-A 325 Webcam	53X27AA,53X27UT
HP 14 Convertible Laptop Backpack Tote	9C2H1AA
HP 14 Modular Laptop Sleeve	9J499AA
HP 15.6 Modular Laptop Backpack	9J496AA
HP 15.6 Modular Laptop Bag	9J497AA
HP 15.6 Modular Laptop Sleeve	9J498AA
HP Campus Core 16 blue Laptop Backpack	B9RB4AA
HP Campus Core 16 green Laptop Backpack	B9RB5AA
HP Convertible Laptop Stand	9C2H2AA
HP Everyday 14 odyssey gray Laptop Bag	A08KJAA
HP Everyday 14 odyssey gray Laptop Briefcase	A08KGAA,A08KGUT
HP Everyday 16 odyssey gray Laptop Backpack	A08KLAA,A08KLUT
HP Everyday 16 odyssey gray Laptop Bag	A08KKAA
HP Everyday 16 odyssey gray Laptop Briefcase	A08KHAA,A08KHUT
HP Modern 14-inch moonless Night Laptop Briefcase	CJ8D0AA
HP Modern 14-inch navy blazer Laptop Briefcase	CJ8F8AA
HP Prelude 15.6 Backpack	1E7D6AA,1E7D6UT,50P32AA
HP Prelude 15.6 Top Load	1E7D7AA,50P31AA
HP Prelude Pro Recycled 15.6 Backpack	1X644AA,1X644UT
HP Prelude Pro Recycled 15.6 Top Load	1X645AA,1X645UT
HP Protective 13-14 atmospheric blue Laptop Sleeve	C3TR3UT
HP Protective 13-14 meteor silver Laptop Sleeve	C3TR2UT
HP Renew Business 14.1 Laptop Bag	3E5F9AA,3E5F9UT
HP Renew Business 14.1 Laptop Sleeve	3E2U7AA,3E2U7UT
HP Renew Business 15.6 Laptop Bag	3E5F8AA,3E5F8UT
HP Renew Business 17.3 Laptop Backpack	3E2U5AA,3E2U5UT
HP Renew Business 17.3 Laptop Bag	3E2U6AA,3E2U6UT
HP Renew Executive 14.1 Laptop Sleeve	6B8Y3AA
HP Renew Executive 16 Laptop Backpack	6B8Y1AA,6B8Y1UT
HP Renew Executive 16 Laptop Bag	6B8Y2AA
HP Travel 18 Liter 15.6 iron gray Laptop Backpack	6H2D9AA
HP Travel 25 Liter 15.6 iron gray Laptop Backpack	6H2D8AA
HP Travel Plus 15 Liter 14 Laptop Bag	A2CE2AA



Commodity	HP Travel Plus 22 Liter 16 Laptop Bag	A2CE1AA	
	HP Travel Plus 30 Liter 17 Laptop Backpack	A2CE0AA	
	HP USB DVD-Writer External ODD	F2B56AA,F2B56UT,Y3T76AA	
	HP 14-inch Widescreen Laptop Privacy Filter	BH0M6AA	
	HP Combination Nano Cable Lock	63B28AA,63B28UT	
	HP Essential Combination Nano Cable Lock	63B31AA,63B31UT	
	HP Nano Keyed Cable Lock	1AJ39AA,1AJ39UT	
Docking	HP Nano Master Keyed Cable Lock	1AJ40AA,1AJ40UT	
	HP SureKey Standard/Nano/Wedge Cable Lock	6UW42AA,6UW42UT	
	HP Thunderbolt™ 100W G6 Dock	9X472AA,9X472UT	
	HP Thunderbolt™ 180W G6 Dock	9X481AA,9X481UT	
Hub	HP Thunderbolt™ 280W G6 Dock	AW5L5AA,AW5M5UT	
	HP USB-C™ 100W G6 Dock	9X3V1AA,9X3V1UT	
Keyboard	HP Portable USB-C Hub	B8SU8AA,B8SU8UT	
	HP USB-C to USB-A Hub	Z6A00AA,Z6A00UT	
	HP 125 G2 Wired Keyboard	AY2Y7AA	
	HP 125 Wired Keyboard	266C9AA,266C9UT	
	HP 225 Wireless Keyboard	805T1AA,805T1UT	
	HP 320K G2 Wired Keyboard	9SR37UT	
	HP 320K USB Wired Keyboard	9SR37AA,9SR37UT	
	HP 355 Compact Multi-Device Keyboard	692S9AA,692S9UT	
	HP 405 Backlit Wired Keyboard	7N7C1AA,7N7C1UT	
	HP 435 Programmable Wireless Keypad	7N7C3AA	
	HP 475 Dual-Mode Wireless Keyboard	7N7B9AA,7N7B9UT	
	HP 485 Comfort Wired Keyboard	8T6M2AA	
	HP 495K Multi-Device Keyboard	BD5F5AA,BD5F5UT	
	HP 585K Multi-Device Keyboard with Palm Rest	BD5F7AA	
	HP 685 Comfort Dual-Mode Keyboard	8T6L9AA,8T6L9UT	
	HP 725 Multi-Device Rechargeable Wireless Keyboard	9T5B2AA	
	HP 965 black Ergonomic Wireless Keyboard	7E756AA	
	HP 975 Dual-Mode USB+Bluetooth Wireless Keyboard	3Z726AA,3Z726UT	
	Keyboard & Mouse Combo	HP 225 Wired Mouse and Keyboard Combo	286J4AA,286J4UT
		HP 225 Wired Mouse and Keyboard Combo	AX2Y7AA



	HP 225 Wired Mouse and Keyboard Combo Cashmere White	AW5S6AA
	HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA,1Y4D0UT
	HP 685 Comfort Dual-Mode Keyboard and Mouse Combo	8T6L7AA,8T6L7UT
	HP 725 Multi-Device Rechargeable Wireless Keyboard and Mouse Combo	9T5B0AA,9T5B0UT
	HP Multi-Device Dual-Mode Mouse and Keyboard Combo 495C	BE1Q0UT
	HP Multi-Device Dual-Mode Mouse and Keyboard Combo 495C White	BE1M6AA
	HP Multi-Device Dual-Mode Mouse and Keyboard Combo with Palm Rest 585C	BD5F3AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA,9SR36UT
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36UT
Monitor	HP Series 7 Pro 27 4K Conferencing Monitor	8K135AA
	HP Series 7 Pro 27 4K Thunderbolt 4 Monitor	8J9G2AA
	HP Series 7 Pro 27 QHD Thunderbolt 4 Monitor	8J9E6AA,8J9E6UT
	HP Series 7 Pro 31.5 4K Thunderbolt 4 Docking Monitor	B7JM6AA
	HP Series 7 Pro 31.5 4K Thunderbolt 4 Monitor	8Y2K9AA
	HP Series 7 Pro 34 WQHD Conferencing Monitor	8K157AA,8K157UT
	HP Series 7 Pro 37.5 WQHD+ Thunderbolt 4 Monitor	8K167AA
Mouse	HP 105 Black Wired Mouse	822M9AA,822M9UT
	HP 105 Mouse Pad	8X595AA
	HP 125 Wired Mouse	265A9AA,265A9UT
	HP 128 Laser Wired Mouse	265D9AA,265D9UT
	HP 205 Desk Mat	8X597AA
	HP 235 Slim Wireless Mouse	4E407AA,4E407UT
	HP 245 Black Bluetooth Mouse	81S67AA,81S67UT
	HP 255 Dual Wireless Mouse	8R3U1AA,8R3U1UT
	HP 285 Silent Wireless Mouse	6G4E6AA
	HP 320M Wired Mouse	9VA80AA,9VA80UT
	HP 405 Quiet Black Wireless Mouse	AZ7B3AA
	HP 425 Programmable Wireless Mouse	7M1D5AA
	HP 435 Multi-Device Wireless Mouse	3B4Q5AA,3B4Q5UT
	HP 515 Ultra-Fast Rechargeable Wireless Mouse	9C2F7AA



Power

HP 685 Comfort Dual-Mode Mouse	8T6M0AA,8T6M0UT
HP 695 Qi-Charging Wireless Mouse	8F1Y4AA
HP 705 Rechargeable Wireless Mouse	AZ7B1AA
HP 715 Rechargeable Multi-Device Bluetooth Mouse	6E6F0AA,6E6F0UT
HP 925 Ergonomic Vertical Wireless Mouse	6H1A5AA
HP Tilt Ergonomic Mouse 725M	BH0Z5AA
HP Travel USB Mouse	G1K28AA
HP Ultra-Fast Scroll Wireless Mouse 785M	B8YX4AA
HP 110W USB-C Laptop Charger	8B3Y2AA,8B3Y2UT
HP 140W USB-C Laptop Charger	B7NK0AA



CHANGELOG

Date of change	Version History		Description of change
	V1		

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

